

# Intrinsically-Safe Phone Isolation Barrier Unit

By GAI-Tronics  
Catalog # 263-000

For applications requiring just a few phones, we recommend that the Intrinsically-Safe Telephones be purchased on an “individual” basis. Each phone (Model 262-001 or 272-001) should be ordered with its own wall-mountable Isolation Barrier Unit (Model 263-000). The Isolation Barrier Unit houses both the PCBA and the Power Supply (suitable for 110/220 VAC) for the telephone. For convenience, a single model number has been established to order an indoor (Model 261-001) or weatherproof (Model 271-001) combination of these units.



## General

Color	Gray
Connectivity Options	Analog
Mount location	Surface-Mount
Signal Type	Analog
Weather Rating	Type 12

## Dimensions

Dimensions	7.46 in x 13.16 in x 9.39 in
Height	9.39 in
Length	7.46 in
Weight	8.5 lb
Width	13.16 in

## Electrical Ratings

Signal	Phone Line
--------	------------

## Certifications And Compliance

Certification	UL/CSA, FCC, IC
---------------	-----------------

## Product Assets

- [Brochures - Rugged Telephone Brochure](#)
- [Installation Manuals - Intrinsically-Safe Telephones \(Model 262-001 and 272-001\)](#)
- [Installation Manuals - Model 263 - Isolation Barrier Unit](#)
- [Literature - Intrinsically Safe Telephones](#)