

SMART UL Class I Div 1 Telephone

By GAI-Tronics
Catalog # 352-101

SMART UL Class I Div 1 Telephone: for users utilizing a conventional PABX technology, GAI-Tronics Self Monitoring and Reporting Technology (SMART) offers event and fault reporting over a standard analog line. SMART models are UL approved to Class I Division 1 Groups B, C, & D, Class II Groups F & G and Class III, Type 4X, and ABS Type Approved.



General

Color	Gray
Connectivity Options	SMART
Mount location	Surface-Mount
Output Level Ringer	External required
Signal Type	Analog
Weather Rating	Type 4X

Dimensions

Cubic Capacity	1175.265 cu.in
Depth	9.36
Height	12.25 in
Weight	28 lb
Width	10.25 in

Electrical Ratings

Signal	Phone Line
--------	------------

Certifications and Compliance

Certification	<ul style="list-style-type: none"> • UL • cUL
Compliance	Telecoms Compliance to Standards: FCC CFR 47 Part 15
Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Division 1, Groups B, C, & D • Class II, Division 1, Groups F & G • Class III, Division 1

Product Assets

[Brochures - Rugged Telephone Brochure](#)
[Installation Manuals - Division 1 SMART Hazardous Area Telephones \(Model 352-101, 352-102, 352-103, and 352-104\)](#)
[Literature - UL Class I Division 1 Telephones \(VoIP / SMART / Analog\)](#)
[Literature - Telephone Management Application \(TMA\)](#)