

SMART UL Class I Div 1 Telephone

By GAI-Tronics Catalog # 352-101

SMART UL Class I Div 1 Telephone: for users utilizing a conventional PABX technology, GAI-Tronics Self Monitoring and Reporting Technology (SMART) offers event and fault reporting over a standard analog line. SMART models are UL approved to Class I Division 1 Groups B, C, & D, Class II Groups F & G and Class III, Type 4X, and ABS Type Approved.



General

Color Gray
Connectivity Options SMART

Mount location Surface-Mount
Output Level Ringer External required

Signal Type Analog
Weather Rating Type 4X

Dimensions

Cubic Capacity 1175.265 cu.in

 Depth
 9.36

 Height
 12.25 in

 Weight
 28 lb

 Width
 10.25 in

Electrical Ratings

Signal Phone Line

Certifications And Compliance

Certification UL

cUL

Compliance Telecoms Compliance to

Standards: FCC CFR 47 Part 15

Hazardous Rating(s) Class I, Division 1, Groups B, C,

& D

Class II, Division 1, Groups F & G

Class III, Division 1

Product Assets

Brochures - Rugged Telephone Brochure Installation Manuals - Division 1 SMART Hazardous Area Telephones (Model 352-101, 352-102, 352-103, and 352-104) Literature - UL Class I Division 1 Telephones (VoIP / SMART / Analog)

Literature - Telephone Management Application (TMA)

