

RED ALERT® Emergency Telephone - Model 397-002

By GAI-Tronics
Catalog # 397-002

GAI-TRONICS' RED ALERT® Emergency Telephones are designed to provide clear and reliable communications in almost any environment. The Model 397-00x is considered to be Type-3R weatherproof compliant when installed in a GAI-Tronics surface-mount enclosure, free-standing stanchion, wall-mount stanchion or simply recessed into an existing wall.



Features

- Weather-resistant (Type 3R) Flush-Mount Design
- Telephone Line Powered, (No Battery or External Power Required for Telephone Operation)
- Large “Palm” Activation HELP Pushbutton For Emergency Call
- Standard or SMART Operation
- Auto Answer (with Silent Monitoring)
- (2) Programmable Auxiliary Outputs for Peripheral Equipment Control
- Operating Range of -20°C to +60°C
- Call Received When Lit LED
- 3-Number Rollover
- UL/CSA 60950 Compliant
- FCC Part 68 Certified
- ADA Compliant
- Monitored by TMA (Telephone Management Application) Software
- Voice Annunciation Option

General

| | |
|----------------------|----------------------|
| Color | Silver |
| Connectivity Options | Analog |
| Mount location | Flush-Mount |
| Output Level Speaker | 87 dB @ 1 M |
| Signal Type | Analog |
| Type | Emergency Telephones |
| Weather Rating | Type 3R |

Dimensions

| | |
|------------|-----------------------------|
| Dimensions | 2.38 in x 10.0 in x 12.0 in |
| Height | 12 in |
| Length | 2.38 in |
| Weight | 6.5 lb |
| Width | 10 in |

Electrical Ratings

| | |
|--------|------------|
| Signal | Phone Line |
|--------|------------|

Certifications And Compliance

| | |
|------------------|-----------------|
| Certified Listed | UL/CSA, FCC, IC |
|------------------|-----------------|

Product Assets

- [Brochures - Red Alert Telephone Brochure](#)
- [Installation Manuals - RED ALERT® 300 Series Emergency Telephone Manual](#)
- [Literature - RED ALERT Hands-free Telephones](#)
- [Literature - Telephone Management Application \(TMA\)](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
GTC-397002-SPEC-EN | REV 6/2024