GAI-TRONICS

RED ALERT® VolP Emergency Telephones - Model 397-710

Bv GAI-Tronics Catalog # 397-710

GAI-TRONICS' RED ALERT® Hands-free VoIP Flush-Mount Telephones are designed to provide direct point-to-point communications between personnel throughout a facility over an existing internet protocol LAN. The VoIP telephones are intended for connection to a 10/100 BaseT Ethernet and operate using power-over-Ethernet or an alternative power source. The VoIP telephone features real-time alarm reporting that enables system supervisors to monitor the phone's activity and address callers needs or maintenance issues immediately.

Features

- Power Over Ethernet or Alternative 24-48 V dc Supply
- SIP Compatible
- Four Inputs and Two Outputs Per Phone
- Auto Answer
- Multicast Capable (Up to 8 Addresses)

Application

Emergency Telephone Communcations (campuses, parking lots, paths)

General

397-710
Silver
VoIP
Front Panel: 14-Gauge Type
304 Brushed Stainless Steel;
Dust Cover: 16-Gauge Cold-
Rolled Steel With Black
Polyurethane Finish
Flush-Mount
-4°F to +131°F / -20°C to +55
°C
87 dB @ 1 M
VoIP - SIP
UL/CSA, FCC
-40° C to +70° C
-4°F to +131°F (-20°C to +55°(
 Emergency Telephones



Weather	Rating
veather	Rating

Dimensions

Dimensions Dimensions - Shipping Height Length Weight Width

2.38 in x 10.0 in x 12.0 in 16.5 x 16.0 x 10.0 12 in 2.38 in 7.2 lb 10 in

HELP Button

Type 3R

Electrical Ratings

Signal Fthernet 24-48 VDC or PoE Voltage Rating Description

Certifications And Compliance

Certification	UL/CSA/FCC
Certified Listed	UL/CSA/FCC
Compliance	FCC CRF 47 Part 15

Product Assets

+55°C)

Brochures - Red Alert Telephone Brochure Configuration Guide - VoIP Telephone Basic Configuration Guide Configuration Guide - VoIP Telephone Configuration Guide: Firmware versions 1193 Telephones (v1.08); 1201 Telephones for Auteldac 6 (v1.08) Literature - VoIP Hands-free Telephones - Flush-mount Specifications - 397710 Video - Gai-Tronics Emergency Phones

