Compact VoIP Hands-free Telephone

By GAI-Tronics
Catalog # 398-711FS

GAI-TRONICS' Compact RED ALERT® Hands-free VoIP Flush-mount Telephones are designed to provide direct point-to-point communications between personnel throughout a facility over an existing internet protocol LAN. The VoIP telephones are intended for connection to a 10/100 BaseT Ethernet and operate using power-over-Ethernet or an alternative power source. The VoIP telephone features real-time alarm reporting that enables system supervisors to monitor the phone's activity and address callers needs or maintenance issues immediately.

Features

- Power Over Ethernet or Alternative 24-48 V dc Supply
- SIP Compatible
- Four Inputs and Two Outputs Per Phone
- Auto Answer
- Multicast Capable (Up to 8 Addresses)

Application

- Rehabilitation Centers
- Correctional Facilities
- Mental Health Facilities

General

Catalog Number	398-711FS
Color	Silver
Connectivity Options	VoIP
Construction	Front Panel: 14-Gauge Type 304 Brushed Stainless Steel; Dust Cover: 16-Gauge Cold-Rolled Steel With Black Polyurethane Finish
Mount location	Flush-Mount
Operating Temperature	-4°F to +131°F / -20°C to +55 °C
Signal Type	VoIP - SIP
Specifications	UL/CSA, FCC
Storage Temperature Range	-40° C to +70° C
Temperature Rating	-4°F to +131°F (-20°C to +55°C)
Type	• Compact Telephones • Keypad

- Behavioral Health Telephones

Dimensions

Dimensions	8.5 in x 6.5 in x 2.37 in
Dimensions - Shipping	13.0 x 12.0 x 8.0
Height	2.37 in
Length	8.5 in
Weight	5 lb
Width	6.5 in

Electrical Ratings

Signal	Ethernet
Voltage Rating Description	24-48 VDC or PoE

Certifications And Compliance

Certification	UL/CSA/FCC
Certified Listed	UL/CSA/FCC
Compliance	FCC CRF 47 Part 15

Product Assets

Brochures - Red Alert Telephone Brochure
Configuration Guide - VoIP Telephone Basic Configuration Guide
Configuration Guide - VoIP Telephone Configuration Guide: Firmware versions 1193 Telephones (v1.08); 1201 Telephones for Auteldac 6 (v1.08)
Literature - Compact Emergency Hands-free Telephones - Models 397-700FS, 397-701FS, 398-701FS
Specifications - 398711FS