GAI-TRONICS

HUBBCOM[™] IP Devices with Temperature Sensing (Desktop, Wall-mount, Handset)

By GAI-Tronics Catalog # GSC1100TS

The HUBBCOM[™] IP device has a multi-functional design, providing solutions for all your control and communication needs. It provides the ability to combine web application control, VoIP SIP telephone operation, speaker broadcasts, and point-topoint serverless IP communication (audio and/or video). HUBBCOM[™] TS devices add another critical function for security applications. This model adds a temperature sensor to the access control feature. After scanning their card, the user simply aligns themselves with the template on the screen and the station will read their temperature. Access will be granted if their temperature is within a programmable range.



- Card Access control with built-in pre-entry temperature check
- Point-to-Point, Serverless Audio & Video
- Paging with Intercom (Soft Zoning, Multiple Conference Calls, Serverless)
- SIP Telephone
- Web Portal Access (applications)
- 7-inch Capacitive Touchscreen
- ONVIF-Compatible HD Camera
- Desktop / Handset
- Intuitive Operation
- 24 V dc or PoE / PoE+ Input
- Integral 2 W Speaker
- 8 Ohm, 8 W Speaker Output
- Two (2) Isolated Volt-free Outputs
- WiFi (802.11 a/b/g/n + MIMO)
- Bluetooth (Version 4.1 + CSA2 support / BLE)

General

Operating Temperature	0° C to 50° C
Power	PoE / PoE+, 802.3af compliant
	(via RJ45)
UPC	850025795395

Dimensions

Weight




Certifications And Compliance

Compliance

FCC CRF 47 Part 15

Product Assets

Brochures - HUBBCOM[™] Solutions Brochure - Communications & Control Brochures - HUBBCOM[™] Solutions Brochure - Communications & Control Catalogs - Transportation - Rail Industry Installation Manuals - HUBBCOM[™] Dual-Port Desktop/Wallmount Smart Controllers Installation Manuals - ADDENDUM-HUBBCOM[™] Temperature Sensor Configuration and Operation Literature - HUBBCOM[™] IP Devices with Temperature Sensing Video - HUBBCOM[™] Temperature Sensing



©2024 Hubbell Incorporated. All rights reserved GTC-GSC1100TS-SPEC-EN | REV 6/2024