

15 kV Insulating Cap, Insulated Cuff

By Hubbell Power Systems
Catalog # 2151CI

Load Break Insulating Cap with Insulating Cuff, 200 Amp, 15 kV.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

General

EU RoHS Indicator	No
Type	200Amp Load Break
UPC	096359391562

Dimensions

Dimensions	6.750 in x 3.000 in x 3.000 in
Height	3.000 in
Length	6.750 in
Weight	1.250 lb
Width	3.000 in

Electrical Ratings

AC Withstand Voltage (1 min)	34 kV
Basic Impulse Level	95 kV
Corona Extinction (3pC)	11 kV
Current Rating	200 A
kV Class	15 kV

Logistics

Pallet Quantity	800
Standard Package	25

Product Assets

[Catalogs - Cable Accessories \(C7\)](#)
[Installation Manuals - 200 Amp, 15kV & 25kV Class Insulating Caps \(IS-200IC\)](#)
[Sales Drawings - Insulating Cap 200A 15 KV \(2151CI\)](#)
[Test Documents - ANSI/IEEE Design Test Report - 15kV 200A Loadbreak Separable Connectors \(G11-12-01\)](#)
[Video - Grease Best PRactices \(HPS_CA_UTL_VI_EN_00030\)](#)