

35 kV, Load Break Elbow w/ Bimetal Contact, Shield Adapter Kit

By Hubbell Power Systems
Catalog # [236LE55S](#)

Load Break Elbow, 200 Amp, 35 kV, Long Bimetal Contact, Shield Adapter Kit, Cable Insulation Diameter range = 1.020 - 1.310 inches, 2/0 Solid or Compacted and 1/0 Stranded or Compressed



*Representative Image

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

General

Connector Type	Bi-Metal
PROBELOK® Connectors	No
Type	200Amp Load Break
With Seal Kit	Yes
With Test Point	No

Dimensions

Cable Insulation Diameter Maximum	1.310 in
Cable Insulation Diameter Minimum	1.020 in
Weight	6.000 lb

Electrical Ratings

AC Withstand Voltage (1 min)	50 kV
Amperage Rating	200 A
Basic Impulse Level	150 kV
Corona Extinction (3pC)	26 kV
Current Rating	200 A
DC Withstand Voltage (15 min)	103 kV
Voltage Rating	35 kV
kV Class	Large Interface 35 kV

Conductor Related

Cable Insulation Diameter Range	1.020 - 1.310
Solid or Compacted Conductor	2/0
Stranded or Compressed Conductor	1/0

Logistics

Pallet Quantity	108
Standard Package	20

Product Assets

- [Catalogs - Cable Accessories \(C7\)](#)
- [Literature - Loadbreak Elbow Infographic \(GR03087E\)](#)
- [SDS - Safety Data Sheet - Versilube G661 Silicone Compound](#)
- [Video - 200A Loadbreak Elbow Fault Closure \(VI03045E\)](#)
- [Video - Grease Best Practices \(HPS_CA_UTL_VI_EN_00030\)](#)