

# 15 kV LRTP Kit w/ Shield Adapter Kit

By Hubbell Power Systems Catalog # 615LRTPG29S

15 kV 600 Amp Load Break Reducing Tap Plug Kit. Cable insulation range 0.760 in - 0.950 in. Kit includes T-body, insulating plug with cap, compression lug, threaded stud, cable adapter, and shield adapter kit



\*Representative Image

## **Features**

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, shear bolt connector, cold shrink jacket seal kit or shield adapter kit

10.000 lb

## General

Connector Type	Aluminum Threaded
Туре	600Amp Dead Break
With Seal Kit	Yes
With Test Point	No

## Dimensions

Weight

Electrical Ratings

AC Withstand Voltage (1 min)	34 kV
Basic Impulse Level	95 kV
Corona Extinction (3pC)	11 kV
Current Rating	200 A
kV Class	15 kV

## **Conductor Related**

Solid or Compacted350ConductorStranded or Compressed300ConductorConductorStranded or Compressed

## Logistics

Standard Package

## **Product Assets**

Catalogs - Cable Accessories (C7) Test Documents - Cable Accessories Test Report - 15kV & 25kV 600A (CH-9904) Video - Grease Best PRactices (HPS\_CA\_UTL\_VI\_EN\_00030)

1

#### **Related Products**

BTW1575F12 BTW1575F12

©2024 Hubbell Incorporated. All rights reserved. HUBB-615LRTPG29S-SPEC-EN | REV 1/2024