

25/28 kV Elbow Tap Plug Kit, with Shield Adapter Kit

By Hubbell Power Systems Catalog # 625ETPJ24S

 $25/28~\rm kV$ 600 Amp Elbow Tap Plug Kit. Cable insulation range 0.980 in - 1.180 in. Kit includes T-body, insulating plug with cap, compression lug, threaded stud, cable adapter, and shield adapter kit



*Representative Image

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, shear bolt connector, cold shrink jacket seal kit or shield adapter kit

General

Connector Type Aluminum

Type 600Amp Dead Break

With Seal Kit Yes
With Test Point No

Dimensions

Weight 9.150 lb

Electrical Ratings

AC Withstand Voltage (1 min) 40 kV
Basic Impulse Level 125 kV
Corona Extinction (3pC) 19 kV
Current Rating 200 A
kV Class 25/28 kV

Conductor Related

Solid or Compacted 2/0 Conductor Stranded or Compressed 1/0

Conductor

Logistics

Standard Package 1

Product Assets

Catalogs - Cable Accessories (C7)

Test Documents - Cable Accessories Test Report - 15kV & 25kV

600A (CH-9904)

Video - Grease Best PRactices (HPS_CA_UTL_VI_EN_00030)

Related Products

BTW1575F12 BTW1575F12

