

## Cable Adapter

By Hubbell Power Systems  
Catalog # [635CAD](#)

35kV 600/900A Cable Adapter, Cable Insulation Diameter  
Range = 0.750 - 0.985 Inches



### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Stepped design

### General

Type Adapters

### Dimensions

Cable Insulation Diameter Maximum	0.985 in
Cable Insulation Diameter Minimum	0.75 in

### Electrical Ratings

AC Withstand Voltage (1 min)	50 kV
Basic Impulse Level	200 kV
Corona Extinction (3pC)	26 kV
kV Class	35 kV

### Conductor Related

Cable Insulation Diameter Range	0.75 - 0.985
------------------------------------	--------------

### Logistics

Standard Package	12
------------------	----

### Product Assets

[Catalogs - Cable Accessories \(C7\)](#)  
[Installation Manuals - IS635BT Installation & Operating Instructions \(TD03052E\\_IS635BT\)](#)  
[Sales Drawings - 35kV Cable Adapters \(635CA\)](#)  
[SDS - Safety Data Sheet - Versilube G661 Silicone Compound](#)  
[Test Documents - 35kV Class 600 Deadbreak Connector Test Report](#)  
[Video - Grease Best PRactices \(HPS\\_CA\\_UTL\\_VI\\_EN\\_00030\)](#)