

## Cable Adapter

By Hubbell Power Systems  
Catalog # [635CAL](#)

35kV 600/900A Cable Adapter, Cable Insulation Diameter  
Range = 1.285 - 1.395 Inches



### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Stepped design

### General

Type Adapters  
UPC 096359752950

### Dimensions

Cable Insulation Diameter  
Maximum 1.395 in  
Cable Insulation Diameter  
Minimum 1.285 in

### Electrical Ratings

AC Withstand Voltage (1 min) 50 kV  
Basic Impulse Level 200 kV  
Corona Extinction (3pC) 26 kV  
kV Class 35 kV

### Conductor Related

Cable Insulation Diameter  
Range 1.285 - 1.395

### Logistics

Pallet Quantity 1536  
Standard Package 12

### Product Assets

[Catalogs - Cable Accessories \(C7\)](#)  
[Installation Manuals - IS635BT Installation & Operating Instructions \(TD03052E\\_IS635BT\)](#)  
[Sales Drawings - 35kV Cable Adapters \(635CA\)](#)  
[SDS - Safety Data Sheet - Versilube G661 Silicone Compound](#)  
[Test Documents - 35kV Class 600 Deadbreak Connector Test Report](#)  
[Video - Grease Best Practices \(HPS\\_CA\\_UTL\\_VI\\_EN\\_00030\)](#)