HUBBELL Power Systems

15 kV, Load Break Elbow w/ Bimetal Contact, Seal Kit

By Hubbell Power Systems Catalog # 215LE57J

Load Break Elbow, 200 Amp, 15 kV, Long Bimetal Contact, Cable Insulation Diameter range = 0.760 - 1.135 inches, 4/0 Solid or Compacted and 3/0 Stranded or Compressed, Seal Kit

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

General

Catalog Number	215LE57J
Connector Type	Bi-Metal
EU RoHS Indicator	No
Integral Seal	No
PROBELOK ? Connectors	No

Type 200Amp Load Break UPC 096359573685

With Seal Kit Yes
With Test Point No

Dimensions

Cable Insulation Diameter	1.135 in
Maximum	

Cable Insulation Diameter 0.76 in

Minimum

Weight 3.25 lb

Electrical Ratings

AC Withstand Voltage (1 min) 34 kV
Basic Impulse Level 95 kV
Corona Extinction (3pC) 11 kV
Current Rating 200 A



*Representative Image

kV Class 15 kV

Conductor Related

Cable Insulation Diameter 0.760 - 1.135

Range

Solid or Compacted Conductor 4/0 Stranded or Compressed 3/0

Conductor

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

Logistics

Pallet Quantity 120 Standard Package 20

Product Assets

Catalogs - Cable Accessories

Installation Manuals - Recommended Crimp Tools and Dies for

200A Elbow Bi-Metal Connectors

Installation Manuals - 200A, 15kV & 25kV Class Elbows

Literature - Loadbreak Elbow Infographic

Sales Drawings - Elbow, 200A 15 kV

SDS - VERSILUBE G661 SILICONE COMPOUND

Specifications - 215LE57J

Test Documents - ANSI/IEEE Design Test Report - 15kV 200A

Loadbreak Separable Connectors

Video - Hubbell Power Systems In Depth: Proper Torque for

Underground Cable Accessories

Video - Hubbell Power Systems 15kv & 25kv 200A Redesigned

Flhow

Video - Hubbell Power Systems 200A Loadbreak Elbow

Installation