

35 kV, Load Break Elbow w/ ProbeLok Bimetal Contact

By Hubbell Power Systems
Catalog # [236LE55P](#)

Load Break Elbow, 200 Amp, 35 kV, Long ProbeLok Bimetal Contact, Cable Insulation Diameter range = 1.020 - 1.310 inches, 2/0 Solid or Compacted and 1/0 Stranded or Compressed



*Representative Image

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

General

Catalog Number	236LE55P
Connector Type	ProbeLok Bi-Metal
Type	200Amp Load Break
With Seal Kit	No
With Test Point	No

Dimensions

Cable Insulation Diameter Maximum	1.31 in
Cable Insulation Diameter Minimum	1.02 in
Weight	5.5 lb

Electrical Ratings

AC Withstand Voltage (1 min)	50 kV
Basic Impulse Level	150 kV
Corona Extinction (3pC)	26 kV
Current Rating	200 A
kV Class	Large Interface 35 kV

Conductor Related

Cable Insulation Diameter Range	1.020 - 1.310
Solid or Compacted Conductor	2/0
Stranded or Compressed Conductor	1/0

Logistics

Pallet Quantity	108
Standard Package	20

Product Assets

[Catalogs - Cable Accessories](#)
[Installation Manuals - Recommended Crimp Tools and Dies for 200A Elbow Bi-Metal Connectors](#)
[Installation Manuals - Loadbreak Connector 200A, 35kV Class Elbow](#)
[Literature - ProbeLok® connectors](#)
[Literature - Loadbreak Elbow Infographic](#)
[SDS - VERSILUBE G661 SILICONE COMPOUND](#)
[Specifications - 236LE55P](#)
[Test Documents - ProbeLock](#)
[Test Documents - Separable Connectors 35kV 200 A](#)
[Video - Hubbell Power Systems In Depth: Proper Torque for Underground Cable Accessories](#)
[Video - Hubbell Power Systems 15kv & 25kv 200A Redesigned Elbow](#)
[Video - Hubbell Power Systems 200A Loadbreak Elbow Installation](#)