

EXB explosionproof and flameproof bolted enclosure, 8 X 12 X 8, Class I, II, III, BCDEFG, Cast Aluminum, Type 4,

By Killark Catalog # EXB-8128 N34

EXB Series, 8 X 12 X 8, Class I, II, III, BCDEFG, Cast Aluminum, Type 4, Bolted Enclosure



*Representative Image

Features

- · High strength, lighter weight, corrosion resistant copper free cast aluminum construction.
- Reduced number of cover bolts.
- Cover o-ring, Nitrile (BUNA-N) material, supplied standard supplied standard for a Type 4X rating.
- Mounting lugs are bi-directional, bolt on, made from ductile aluminum alloy.
- Back pan mounting holes predrilled.
- Conduit and device openings factory or field installed.
- Aluminum hinges and stainless steel hardware standard on mid to large size boxes.
- Recessed flange notches to allow for easier cover opening.

Application

• Locations made hazardous due to the presence of flammable gases or vapors, combustible dust, or easily ignitable fibers and flyings, and areas which are subject to corrosion, weather, and dampness. Petroleum refineries, chemical and petrochemical plants w

General

Catalog Number Color Cover Type EU RoHS Indicator Material Series	EXB-8128 N34 Gray Bolted Contact Manufacturer Aluminum, Copper Free (less than 4/10 of 1%) EXB	Conformity Certifications - EXB & EXBLT Series Enclosures ATEX Certificate Certifications - EXB Series Auxiliary Devices UL Certification Certifications - EXB & EXBLT Series CSA Certificate of Conformance Certifications - EXB & EXBLT Series Controllers ATEX Certificate Certifications - EXB/EXBLT Series Enclosure UKCA Certificate
Size	ель 8″ x 12″ x 8″	Certifications - EXB & EXBLT Series Controllers IECEx Certification
Type UPC	Junction Box 783936119304	Certification Certifications - EXB & EXBLT Series Enclosures IECEx Certification
Dimensions		Certifications - EXB/EXBLT Series Controller UKCA Certificate Certifications - EXB & EXBLT Series UL Certificate of Compliance
Dimensions	10.7 in x 13.25 in x 17.25 in	Customer Notices - Prop 65 Notice
Gross Weight with Packaging	67	Engineering Drawing - EXB-8128 N34 Engineering Drawing
Height	17.25 in	Installation Manuals - EXB Series IOM K0983
Length	10.7 in	Installation Manuals - EXB Series Drilling & Tapping IOM K1156
Width	13.25 in	Sales Drawings - EXB-8128 N34 Sales Drawing



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved KILL-EXB8128N34-SPEC-EN | REV 3/2025

Certifications And Compliance

ATEX File Number	PTB 07 ATEX 1025U / PTB 07 ATEX 1024
Buy America(n) Qualified CSA File Number Hazardous Rating(s)	Contact Manufacturer LR11716 • Class I, Divisions 1 & 2,
	 Groups B, C, D Class I, Zones 1 & 2, Groups IIB+H2, IIA Class II, Divisions 1 & 2, Groups E, F, G Class III, Divisions 1 & 2
IECEx File Number	EC E x 07.0022U / IEC E x 07.0023
Nema Rating UL File Number	3, 4, 4X E10514 / E83696 / E12379

Product Assets

3D Models - KIL EXB-8128 N34

Catalog Page - EXBLT Series Catalog Pages

Catalogs - Killark Catalog Certifications - EXB & EXBLT Series Enclosures Declaration of Sales Drawings - EXB-8128 N34 Sales Drawing

Specifications - EXB8128N34