



HKH Series Control Station, Three Momentary Push Buttons- Panel Mount- M20 - Stainless Steel 1c

By Killark
Catalog # [HKHMOD000028](#)

HKH Three Momentary Push Buttons- Panel Mount- M20 - Stainless Steel 1c



Features

- Size 1 Control Stations available as 1a, 1b, & 1c as standard catalog number offerings for 1, 2 & 3 device openings and will accept 2-M20 entries in either end.
- Ammeters available in 1b & 1c.
- Size 2 Enclosures available as 2a & 2c for 2, 4 & 6 device entries in cover with ability to accept 2-M25 entries in either end.
- Operating Temperature of -50°C to +60°C.
- Explosion Protected contact blocks 690 VAC N.O. & N.C. capable of 20 Amps for Switching Duty and HP Ratings up to 1HP.
- LED Pilot Light modules for 12-250V AC/ DC for UL applications. 12-254V AC/DC for IEC applications.
- Contacts & Pilot lights can be mounted inside enclosure on Din Rail or in cover to the actuator.
- Accessories available for Lockout/Tag Out functions made in 316 stainless steel.

Application

Hazardous and corrosive environments due to the presence of flammable gases or vapors, combustible dusts or ignitable fiber or flyings, Installations at petroleum refineries, chemical and petrochemical plants and other processing or storage facilities where similar hazards exist, Use in conjunction with motor starters or contactors for remote control of motors

General

Action	Momentary
Actuator	Three Pushbuttons
Ambient Temp. Range	-50 °C to 60 °C
Color	Choice of Red, Green, Black
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	1
Material	Plastic
Mounting Type	Wall
Operating Temperature Range Celcius	-50°C to 60°C
Series	HKH
UPC	783936130491

Dimensions

Depth	4.25
Hub Size	M20
Weight	1.88 lb

Certifications and Compliance

ATEX File Number	1405X
Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Division 2, Groups A, B, C, D • Class II, Division 1, Groups E, F, G (Canada Only) • Class II, Division 2, Groups E, F, G • Class III, Divisions 1 & 2 • Zones 1 & 2 • Zones 21 & 22
IECEX File Number	15.0054X
Nema Rating	3, 4, 4X, 12, 13
UL File Number	E53360

Product Assets

- [3D Models - KIL_HKHMOD000028](#)
- [Brochures - HKH Brochure](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - HKH Series E-Stop Assemblies Attestation of Conformity](#)
- [Certifications - HKH Inmetro Certificate of Conformity](#)
- [Certifications - HKH Series Control Stations UL Certification](#)
- [Certifications - HKH Series Actuators, Pilotlights, & Plugs Declaration of Conformity](#)
- [Certifications - HKH Series Control Stations Declaration of Conformity](#)
- [Certifications - HKH Series Control Stations UKCA Certificate](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - HKH Series Control Stations Installation Manual K1466](#)
- [Sales Drawings - HKHMOD000028 Sales Drawing \(PDF\)](#)
- [Sales Drawings - HKHMOD000028 Sales Drawing \(DXF\)](#)

Electrical Ratings

Amperage Rating	20 A
Frequency Rating	50/60 Hz



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
KILL-HKHM000028-SPEC-EN | REV 7/2023