

VML-X Series LED Area light 75 Watt, 120-277VAC, 9000 Lumen Driver Tank

By Killark Catalog # VML1X930G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.



- Energy Efficient and Long Life LED's
- · Walkway Optic patterns
- Easy Retrofit to Competitors
- · Lighter Weight
- · LED Color of 5000K with 80 CRI
- Wildlife Friendly Color options

Application

Class I Division 2 Hazardous LocationsClass II Hazardous Dust Zone 2 Hazardous LocationsOff and On Shore Oil and GasWet and Marine LocationsFood and BeverageHeavy Industrial

General

Catalog Number VML1X930G Color Temperature 5000 K

Finish Type Powder Epoxy Paint

Light Source LED

Lumen Range 5,000 - 9,000 lm

Lumens9000Optic TypeGlass GlobeSeriesVML-X

UPC 783936185408

Electrical Ratings

Current / Amperage Rating 0.63-0.27 A Frequency Rating 50/60 Hz



Voltage Rating 120-277 VAC Wattage 75 W

Certifications And Compliance

Hazardous Rating(s)

- Class I, Div2, Groups A,B,C,D
- Class I, Zone 2, Groups IIC, IIB. IIA
- Class II, Div. 1&2, Groups E.F.G
- IECEX QPS 15.0006
- Ex ec IIC T4/T3 Gc
- Ex tb IIIC T4/T3 Db
- QPS22ATEX7000

Product Assets

Brochures - VML-X Series for Harsh and Hazardous Environments

Certifications - VMLX/VM4L Series EU Type ATEX Certificate Certifications - VMLX & VM4L Series Attesation of Conformity

Certifications - VMLX Series QPS North American Certification

Certifications - VMLX/VM4L Series ATEX Certificate
Certifications - VMLX & VM4L Series IECEx Certification

Installation Manuals - VMLX Series IOM K1531

Photometry - KIL_VML1X930NDR Photometry - KIL_VML1X930NAR Photometry - KIL_VML1X930N Specifications - VML1X930G

Video - VML-X Features and Benefits

