KILLARK

VML-X Series LED Area light 120 Watt, 120-277VAC, 15000 Lumen 1-1/4" 25° Stanchion Mount

By Killark Catalog # VML2X1530D4G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.

Application

- Class I Division 2 Hazardous Locations
- Class II Hazardous Dust
- Zone 2 Hazardous Locations
- Off and On Shore Oil and Gas
- Wet and Marine Locations
- Food and Beverage
- Heavy Industrial

General

| | | • Ex to IIIC 14/13 Db |
|---------------------------|--------------------|---|
| Catalog Number | VML2X1530D4G | • QPS 22ATEX7000 |
| Color Temperature | 5000 K | |
| Finish Type | Powder Epoxy Paint | Product Assets |
| Light Source | LED | |
| Lumen Range | 12,000 - 18,000 lm | Brochures - VML-X Series Hazardous Location Luminaires |
| Lumens | 15000 | Brochure |
| Mounting Type | 25° Stanchion | Brochures - VML-X Series for Harsh and Hazardous |
| Optic Type | Glass Globe | Environments |
| Series | VML-X | Catalog Page - VML-X Series Catalog Pages |
| | | Catalogs - Killark Catalog |
| Dimensions | | Certifications - VMLX/VM4L Series EU Type ATEX Certificate |
| | | Certifications - VMLX & VM4L Series Attesation of Conformity |
| Hub Size | 1-1/4" | Certifications - VMLX Series QPS North American Certification |
| | | Certifications - VMLX/VM4L Series ATEX Certificate |
| Electrical Ratings | | Certifications - VMLX & VM4L Series IECEx Certification |
| Current / Amperage Rating | 1.00-0.43 A | Installation Manuals - VMLX Series IOM K1531 |
| Frequency Rating | 50-60 Hz | Photometry - KIL VML2X1530N |
| Voltage Rating | 120-277 VAC | Specifications - VML2X1530D4G |
| VUILAYE KALIIIY | IZU-ZI/ VAC | Video - VML-X Features and Benefits |
| | | |



120 W

Certifications And Compliance

Hazardous Rating(s)

- Class I, Div2, Groups A,B,C,D
- Class I, Zone 2, Groups IIC, IIB. IIA
- Class II, Div. 1&2, Groups E.F.G
- IECEx QPS 15.0006
- Ex ec IIC T4/T3 Gc
- Ex th IIIC T4/T3 Db

| ochure |
|--|
| ochures - VML-X Series for Harsh and Hazardous |
| vironments |
| atalog Page - VML-X Series Catalog Pages |
| atalogs - Killark Catalog |
| ertifications - VMLX/VM4L Series EU Type ATEX Certificate |
| ertifications - VMLX & VM4L Series Attesation of Conformity |
| ertifications - VMLX Series QPS North American Certification |
| ertifications - VMLX/VM4L Series ATEX Certificate |
| ertifications - VMLX & VM4L Series IECEx Certification |
| stallation Manuals - VMLX Series IOM K1531 |
| notometry - KIL_VML2X1530N |
| pecifications - VML2X1530D4G |
| deo - VML-X Features and Benefits |
| |
| |



©2025 Hubbell Incorporated. All rights reserved KILL-VML2X1530D4G-SPEC-EN | REV 3/2025