KILLARK®

VML-X Series LED Area light 120 Watt, 120-277VAC, 15000 Lumen 1-1/2" 25° Stanchion Mount

By Killark
Catalog # VML2X1530D5G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.

Application

- Class I Division 2 Hazardous Locations
- Class II Hazardous Dust
- Zone 2 Hazardous Locations
- Off and On Shore Oil and Gas
- Wet and Marine Locations
- Food and Beverage
- Heavy Industrial

General

Catalog Number	VML2X1530D5G
Color Temperature	5000 K
Finish Type	Powder Epoxy Paint
Light Source	LED
Lumen Range	12,000 - 18,000 lm
Lumens	15000
Mounting Type	25° Stanchion
Optic Type	Glass Globe
Series	VML-X

Dimensions

Hub Size	1-1/2"

Electrical Ratings

Current / Amperage Rating	1.00-0.43 A
Frequency Rating	50-60 Hz
Voltage Rating	120-277 VAC

Wattage	120 W

Certifications And Compliance

Hazardous Rating(s)	• Class I, Div2, Groups A,B,C,D
	• Class I, Zone 2, Groups IIC, IIB, IIA
	• Class II, Div. 1&2, Groups E,F,G
	• IECEx QPS 15.0006
	• Ex ec IIC T4/T3 Gc
	• Ex tb IIIC T4/T3 Db
	• QPS 22ATEX7000

Product Assets

Brochures - VML-X Series Hazardous Location Luminaires Brochure
Brochures - VML-X Series for Harsh and Hazardous Environments
Catalog Page - VML-X Series Catalog Pages
Catalogs - Killark Catalog
Certifications - VMLX/VM4L Series EU Type ATEX Certificate
Certifications - VMLX & VM4L Series Attesation of Conformity
Certifications - VMLX Series QPS North American Certification
Certifications - VMLX/VM4L Series ATEX Certificate
Certifications - VMLX & VM4L Series IECEx Certification
Installation Manuals - VMLX Series IOM K1531
Photometry - KIL_VML2X1530N
Specifications - VML2X1530D5G
Video - VML-X Features and Benefits