

VML-X Series LED Area light 120 Watt, 120-277VAC, 15000 Lumen 1-1/2" Straight Stanchion

By Killark

Catalog # VML2X1530S5G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.



Features

Wildlife Friendly Color options

General

Application Class I Division 2 Hazardous

Locations

Class II Hazardous Dust

Zone 2 Hazardous Locations

Off and On Shore Oil and Gas

Wet and Marine Locations

Heavy Industrial

Food and Beverage

VML2X1530S5G

Color Temperature 5000 K

Finish Type Powder Epoxy Paint

Light Source LED

Lumen Range 12,000 - 18,000 lm

Lumens 15000

Mounting Type Straight Stanchion

Optic Type Glass Globe Series VML-X

Dimensions

Catalog Number

Hub Size 1-1/2"

Electrical Ratings

Current / Amperage Rating 1.00-0.43 A
Frequency Rating 50-60 Hz
Voltage Rating 120-277 VAC
Wattage 120 W

Certifications And Compliance

Hazardous Rating(s) Class I, Div2, Groups A,B,C,D

Class I, Zone 2, Groups IIC, IIB,

IΙΑ

Class II, Div. 1&2, Groups E,F,G

IECEX QPS 15.0006

Ex ec IIC T4/T3 Gc

Ex tb IIIC T4/T3 Db

QPS 22ATEX7000

Product Assets

Brochures - VML-X Series for Harsh and Hazardous

Environments

Brochures - VML-X Series Hazardous Location Luminaires

Brochure

Catalog Page - VML-X Series Catalog Pages

Catalogs - Killark Catalog

Certifications - VMLX/VM4L Series EU Type ATEX Certificate

Certifications - VMLX & VM4L Series Attesation of Conformity

Certifications - VMLX & VM4L Series IECEx Certification

Certifications - VMLX/VM4L Series ATEX Certificate

Certifications - VMLX Series QPS North American Certification

Installation Manuals - VMLX Series IOM K1531

Photometry - KIL_VML2X1530N Video - VML-X Features and Benefits



©2024 Hubbell Incorporated. All rights reserved KILL-VML2X1530S5G-SPEC-EN | REV 6/2024