

VML-X Series LED Area light 140 Watt, 120-277VAC, 18000 Lumen 3/4" Wall Bracket

By Killark

Catalog # VML2X1830B2G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.



Features

Wildlife Friendly Color options

General

Class I Division 2 Hazardous Application

Locations

Class II Hazardous Dust

Zone 2 Hazardous Locations

Off and On Shore Oil and Gas

Wet and Marine Locations

Food and Beverage Heavy Industrial

VML2X1830B2G

Color Temperature 5000 K

Finish Type Powder Epoxy Paint

Light Source I FD

Lumen Range 12,000 - 18,000 lm

18000 Lumens Wall Bracket Mounting Type Optic Type Glass Globe VML-X Series

Dimensions

Catalog Number

Hub Size 3/4"

Electrical Ratings

Current / Amperage Rating 1.17-0.51 A Frequency Rating 50-60 Hz Voltage Rating 120-277 VAC Wattage 140 W

Certifications And Compliance

Class I, Div2, Groups A,B,C,D Hazardous Rating(s)

Class I, Zone 2, Groups IIC, IIB,

Class II, Div. 1&2, Groups E,F,G

IECEX QPS 15.0006 Ex ec IIC T4/T3 Gc Ex tb IIIC T4/T3 Db QPS 22ATEX7000

Product Assets

Brochures - VML-X Series for Harsh and Hazardous

Environments

Brochures - VML-X Series Hazardous Location Luminaires

Brochure

Catalog Page - VML-X Series Catalog Pages

Catalogs - Killark Catalog

Certifications - VMLX/VM4L Series EU Type ATEX Certificate

Certifications - VMLX & VM4L Series Attesation of Conformity

Certifications - VMLX & VM4L Series IECEx Certification

Certifications - VMLX/VM4L Series ATEX Certificate

Certifications - VMLX Series QPS North American Certification

Installation Manuals - VMLX Series IOM K1531

Photometry - KIL_VML2X1830N Photometry - KIL_VML2X1830NAR Photometry - KIL VML2X1830NDR Video - VML-X Features and Benefits

