KILLARK®

VML-X Series LED Area light 140 Watt, 120-277VAC, 18000 Lumen 3/4" Cone Mount

By Killark
Catalog # VML2X1830C2G

The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.

Features

Wildlife Friendly Color options

Application

- Class I Division 2 Hazardous Locations
- Class II Hazardous Dust
- Zone 2 Hazardous Locations
- Off and On Shore Oil and Gas
- Wet and Marine Locations
- Food and Beverage
- Heavy Industrial

General

Catalog Number	VML2X1830C2G
Color Temperature	5000 K
Finish Type	Powder Epoxy Paint
Light Source	LED
Lumen Range	12,000 - 18,000 lm
Lumens	18000
Mounting Type	Cone
Optic Type	Glass Globe
Series	VML-X

Dimensions

Hub Size	3/4"

Electrical Ratings

Current / Amperage Rating	1.17-0.51 A
Frequency Rating	50-60 Hz
Voltage Rating	120-277 VAC
Wattage	140 W

Certifications And Compliance

Hazardous Rating(s)

- Class I, Div2, Groups A,B,C,D
- Class I, Zone 2, Groups IIC, IIB, IIA
- Class II, Div. 1&2, Groups E,F,G
- IECEx QPS 15.0006
- Ex ec IIC T4/T3 Gc
- Ex tb IIIC T4/T3 Db
- QPS 22ATEX7000

Product Assets

Brochures - VML-X Series Hazardous Location Luminaires Brochure
Brochures - VML-X Series for Harsh and Hazardous Environments
Catalog Page - VML-X Series Catalog Pages
Catalogs - Killark Catalog
Certifications - VMLX/VM4L Series EU Type ATEX Certificate
Certifications - VMLX & VM4L Series Attesation of Conformity
Certifications - VMLX Series QPS North American Certification
Certifications - VMLX/VM4L Series ATEX Certificate
Certifications - VMLX & VM4L Series IECEx Certification
Installation Manuals - VMLX Series IOM K1531
Photometry - KIL_VML2X1830NAR
Photometry - KIL_VML2X1830NDR
Photometry - KIL_VML2X1830N
Specifications - VML2X1830C2G
Video - VML-X Features and Benefits

©2024 Hubbell Incorporated. All rights reserved