



## VML-X Series LED Area light 250 Watt, 120-277VAC, 28000 Lumen 1" Ceiling Mount

By Killark

Catalog # [VML3X2830X3G](#)



The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.

### Features

- Energy Efficient and Long Life LED's
- Walkway Optic patterns
- Easy Retrofit to Competitors
- Lighter Weight
- LED Color of 5000K with 80 CRI
- Wildlife Friendly Color options

### Application

- Class I Division 2 Hazardous Locations
- Class II Hazardous Dust
- Zone 2 Hazardous Locations
- Off and On Shore Oil and Gas
- Wet and Marine Locations
- Food and Beverage
- Heavy Industrial

### General

Catalog Number	VML3X2830X3G
Color Temperature	5000 K
Finish Type	Powder Epoxy Paint
Light Source	LED
Lumen Range	23,000 - 28,000 lm
Lumens	28000
Mounting Type	Ceiling
Optic Type	Glass Globe
Series	VML-X

### Dimensions

Hub Size	1"
----------	----

### Electrical Ratings

Current / Amperage Rating	2.08-0.09 A
Frequency Rating	50-60 Hz
Voltage Rating	120-277 VAC
Wattage	250 W

### Certifications And Compliance

Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Div2, Groups A,B,C,D</li><li>• Class I, Zone 2, Groups IIC, IIB, IIA</li><li>• Class II, Div. 1&amp;2, Groups E,F,G</li><li>• IECEx QPS 15.0006</li><li>• Ex ec IIC T4/T3 Gc</li><li>• Ex tb IIIC T4/T3 Db</li><li>• QPS 22ATEX7000</li></ul>
---------------------	--

### Product Assets

[Brochures - VML-X Series Hazardous Location Luminaires Brochure](#)

[Brochures - VML-X Series for Harsh and Hazardous Environments](#)

[Catalog Page - VML-X Series Catalog Pages](#)

[Catalogs - Killark Catalog](#)

[Certifications - VMLX/VM4L Series EU Type ATEX Certificate](#)

[Certifications - VMLX & VM4L Series Attestation of Conformity](#)

[Certifications - VMLX Series QPS North American Certification](#)

[Certifications - VMLX/VM4L Series ATEX Certificate](#)

[Certifications - VMLX & VM4L Series IECEx Certification](#)

[Installation Manuals - VMLX Series IOM K1531](#)

[Photometry - KIL\\_VML3X2830NDR](#)

[Photometry - KIL\\_VML3X2830N](#)

[Specifications - VML3X2830X3G](#)

[Video - VML-X Features and Benefits](#)



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
KILL-VML3X2830X3G-SPEC-EN | REV 10/2024