KILLARK®

ENY-2-T - ¾″ ENY Seal Fitting Aluminum with Nipple Male/Female

By Killark
Catalog # ENY-2-T

¾″ ENY Seal Fitting Aluminum with Nipple Male/Female

*Representative Image

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

General

Catalog Number	ENY-2-T
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	ENY
Type	Sealing Fitting With Nipple
UPC	783936110516

Dimensions

Dimensions	5 in x 10 in x 0.1 in
Gross Weight with Packaging	0.55
Height	0.1 in
Hub Size	3/4″
Length	5 in
Weight	1.34 lb
Width	10 in

Certifications And Compliance

CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
UL File Number	E10514

Logistics

Carton Quantity	25

Product Assets

Catalog Page - Fittings: EY Series
Catalogs - Killark Catalog
Certifications - ENY Series & Sealing Compound CSA Certificate
Certifications - EY & EYD Series Sealing Fittings UL Certification
Certifications - ENY Series Sealing Fittings UL Certifications
Customer Notices - Prop 65 Notice
Installation Manuals - Seal Fitting Max Wire Fill IOM K1120
Installation Manuals - ENY Series IOM K1491
Literature - ENY Series Expanded Product Offering
Literature - Hazardous-rated seal-off fittings in expanded trade sizes and with improved design
Specifications - ENY Spec Sheet
Specifications - ENY-2-T Specification Sheet French
Specifications - Sealing Materials Specification Sheet
Specifications - EY-ENY-EYS-EYD Series Sealing Fittings Specification Sheet
Specifications - ENY2T Specification Sheet English
Specifications - Sealing Compound & Packing Fiber Specification Sheet

©2025 Hubbell Incorporated. All rights reserved