KILLARK®

FXCS-1B4-M

By Killark Catalog # FXCS-1B4-M

FXCS Series - Seal-XM - Aluminum Dead-End Momentary Contact Double Push Button Control Station - Factory Sealed - Red And Green Buttons - Hub Size ½" - 2NO/2NC Contact Rating.



Features

- Incorporates Factory Sealed Universal contact blocks and GOB3 LED pilot light devices.
- External sealing fittings typically not required, reducing installation time and cost.
- No seal plate between the electrical device and back box allows direct wiring to contact terminals.
- NEMA 3 weatherproof.
- Grounding boss supplied in the splice box.
- Sold as a complete unit.
- Standard finish is a gray epoxy powder baked on for ultimate corrosion resistance.
- More wiring room in back box.

Application

SEAL-XM Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

General

Action Momentary
Actuator Double Pushbutton
Ambient Temp. Range UL: -25 to 40 °C, CSA: -50 to

40 °C, IEC: -20 to 40 °C EXB

Back Box Type FXB
Color • Green-Red

Vert-Rouge

EU RoHS Indicator Contact Manufacturer

Hub Pattern Dead-End Series Seal-XM

Type • Factory Sealed

• Factory Sealed

UPC 783936105321

Dimensions

Depth 4.28 Hub Size 1/2"

Electrical Ratings

Amperage Rating 10 A Frequency Rating 50/60 Hz

Certifications and Compliance

CSA File Number LR11714, 2493125

Hazardous Rating(s)

• Class I, Divisions 1 & 2,
Groups C, D

• Class I, Zones 1 & 2, Groups IIB, IIA

• Class II, Divisions 1 & 2, Groups E, F, G

• Class III, Divisions 1 & 2

Nema Rating 3

Logistics

Factory Sealed Factory Sealed

Product Assets

Catalogs - Killark Catalog

Certifications - FXCS Series Factory Sealed Control Stations

CSA Certification

Certifications - FXCS & XCS Series Auxiliary Devices UL

Certification

Customer Notices - Prop 65 Notice

Installation Manuals - FXCS Seal-XM IOM K1390

