KILLARK®

MBL101-R5X3 - 100W HPS Fluorescent 120V 1" Ceiling Mount with Glass Refractor

By Killark Catalog # MBL101-R5X3

100W HPS Fluorescent 120V 1" Ceiling Mount with Glass Refractor



Frequency Rating 60 Hz Voltage Rating 120 VAC Wattage 100 W

Certifications And Compliance

Hazardous Rating(s) • Class I, Division 2, Groups A,

1′′

B, C, D

• Class I, Zone 2, Groups IIC, IIB, IIA

• Class II, Divisions 1 & 2, Groups E. F. G

• Class III, Divisions 1 & 2

Logistics

Hub Size

Electrical Ratings

Carton Quantity 1

Product Assets

Customer Notices - Prop 65 Notice Photometry - KIL_MBL10x-R5

Specifications - MB Series Fluorescent Bi-Pin Specification Sheet

Specifications - MBL101-R5X3 Specification Sheet French Specifications - MBL101R5X3 Specification Sheet English

Features

•

•

•

.

General

Catalog Number MBL101-R5X3

EU RoHS Indicator Contact Manufacturer
Finish Type Powder Epoxy Paint
Lamp Type Medium Base

Light Source High Pressure Sodium

Material Aluminum, Copper Free (less

than 4/10 of 1%)

Mounting Type Ceiling

Optic Type Glass Type V Refractor

Series M

UPC 783936993942

Dimensions

