



VML-X Series LED Area light 75 Watt, 120-277VAC, 9000 Lumen 3/4" Ceiling Mount

By Killark

Catalog # [VML1X930X2G](#)



The VML-X Series is an Area Light fixture using energy efficient LED's. The redesigned CertiLite VML-X uses optics on the LED's to direct the light to where it is needed. This fixture is made with a cast copper-free aluminum housing and mount that is suitable for harsh and hazardous environments. The design of this fixture internal heat sink keeps a clean look on the outside of the fixture creating a LED fixture that does not contain external heat fins. Easily Retro fit any old HID or LED fixture to the new VML-X for a cleaner more efficient light.

Application

- Class I Division 2 Hazardous Locations
- Class II Hazardous Dust
- Zone 2 Hazardous Locations
- Off and On Shore Oil and Gas
- Wet and Marine Locations
- Food and Beverage
- Heavy Industrial

General

Catalog Number	VML1X930X2G
Color Temperature	5000 K
Finish Type	Powder Epoxy Paint
Lumen Range	5,000 - 9,000 lm
Lumens	9000
Optic Type	Glass Globe
Series	VML-X

Dimensions

Hub Size	3/4"
----------	------

Electrical Ratings

Current / Amperage Rating	0.63-0.27 A
Frequency Rating	50-60 Hz
Voltage Rating	120-277 VAC
Wattage	75 W

Certifications And Compliance

Hazardous Rating(s)

- Class I, Div2, Groups A,B,C,D
- Class I, Zone 2, Groups IIC, IIB, IIA
- Class II, Div. 1&2, Groups E,F,G
- IECEx QPS 15.0006
- Ex ec IIC T4/T3 Gc
- Ex tb IIIC T4/T3 Db
- QPS 22ATEX7000

Product Assets

[Brochures - VML-X Series Brochure](#)
[Brochures - VML-X Series Brochure French](#)
[Catalog Page - LI KIL CP EN 00043-CANFR](#)
[Catalog Page - LI KIL CP EN 00043-CANEN](#)
[Catalog Page - VML-X Series Catalog Pages](#)
[Certifications - VMLX/VM4L Series EU Type ATEX Certificate](#)
[Certifications - VMLX & VM4L Series Attestation of Conformity](#)
[Certifications - VMLX Series QPS North American Certification](#)
[Certifications - VMLX/VM4L Series ATEX Certificate](#)
[Certifications - VMLX & VM4L Series IECEx Certification](#)
[Installation Manuals - VMLX Series IOM K1531](#)
[Photometry - KIL_VML1X930NDR](#)
[Photometry - KIL_VML1X930NAR](#)
[Photometry - KIL_VML1X930N](#)
[Specifications - VML1X930X2G Specification Sheet French](#)
[Specifications - VML1X930X2G Specification Sheet English](#)
[Video](#)
[Video - VML-X Features and Benefits](#)
[Video](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
KILL_CA-VML1X930X2G-SPEC-EN | REV 4/2025