KILLARK®

VSL1630 - VSL Series - Aluminum 16 Watt Low Wattage Led Luminaire Fixture (Drivers And LED Included) - 120-277VAC At 50/60Hz

By Killark
Catalog # VSL1630

VSL Series - Aluminum 16 Watt Low Wattage Led Luminaire Fixture (Drivers And LED Included) - 120-277VAC At 50/60Hz

Features

- Integral driver – maintains fixture's compact profile to fit in existing spaces
- Ambient suitability -40°C to 55°C
- World Voltage 120 - 277VAC 50/60Hz
- Instant On – Including after power interruption
- Solder-LESS LED Board Connections – Vibration Resistant
- LM80-08 Measurement of lumen maintenance for LED light sources
- LM79-08 Certified "Absolute" Photometry, including Chromaticity Color for Solid State Lighting
- L70 Values - Industry Nomenclature for Hours of use to 70% of Initial Lumens (TM-21+ Cal.)

Application

Killark 'VSL' Series LED fixtures are designed for installations where moisture, dirt, dust, corrosion and vibration may be present, or NEMA 3 and 4 areas where wind, water, snow or high ambients can be expected. VSL's are sized to replace "Utility" type fixtures (incandescent or CFL's) in hallways, closets, elevator pits, docks, stairwells, access tunnels, and mechanical rooms. These fixtures can be used in locations made hazardous by the presence of flammable vapors or gases or combustible dusts as defined by the NEC. Typical applications include manufacturing plants, and certain chemical and petrochemical processing facilities, sewage treatment plants, off-shore and dockside installations, and garage areas

Specifications

EU RoHS Indicator

Hazardous Rating(s)

Contact Manufacturer

- Class I, Division 2, Groups A, B, C, D
- Class I, Zone 2, Groups IIC,IIB,IIA
- Class II, Division 2, Groups F, G
- Class III, Divsions 1 & 2

Current

Frequency Rating	50/60 Hz
Lumens Per Watt	101.6
Wattage	16 W
Voltage Rating	120-277 VAC

Dimensions

Length	8.02 in
Gross Weight with Packaging	5
Width	4.38 in
Height	10.11 in
Dimensions	8.02 in x 4.38 in x 10.11 in

General

Series	VSL Series
Optic Type	Luminaire Only
Color	Gray
Type	Aluminum LED Fixture
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint
UPC	783936090795
Light Source	LED
Mounting Type	Luminaire Only

Operational

Lumen Range	0-2,000 lm
Operating Cycles	10,000 hrs
Lumens	1625

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved