

NOC-3.5S

NONI 3.5" SQUARE CYLINDER FAMILY

ORDERING GUIDE

Examples: NOC-3.5SDL-CHNCSCMBL-SO60930K-DM1NUGT / NOC-3.5SDL-TRM-RPPFRS

CATALOG #

HOUSING

NOC-3.5S		CHN			Optic Type	
Series/Category/Size/Shape	Function	Housing	Canopy	Mounting		
NOC-3.5S Noni Cylinder Family 3.5" Square	DL Downlight	CHN Cylinder Housing	CS Canopy - Standard CC Canopy - Conduit	CMBL Cable/Cord 6ft Black Cord ²	Ultra-Smooth Optic SO60 60° Wall Wash Optic LWLW Lensed Wall Wash ³	
	LW Lensed Wall Wash			CMWH Cable/Cord 6ft White Cord ²		
	CM15BL Cable/Cord 15ft Black Cord					
	CM15WH Cable/Cord 15ft White Cord					
	PR Stem - Rigid (Standard) Nominal 18" length from cylinder top to ceiling ¹					
	PR_ Stem - Rigid (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" ¹					
	P Stem - Swivel (Standard) Nominal 18" length from cylinder top to ceiling ¹					
	P_ Stem - Swivel (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" ¹					
	SU Surface					

CRI/CCT	Driver Options	Control Options	U Voltage	Cylinder Housing Color
927K 90 CRI, 2700K	DM1 0-10V, ELV, TRIAC 1%	N None	U Universal Voltage 120-277V	Texture
930K 90 CRI, 3000K	ERP 0-10V, ELV, TRIAC Dim-to-Dark			WH White
935K 90 CRI, 3500K	PEQOE Lutron Hi-Lume Premier 0.1%			GY Gray
940K 90 CRI, 4000K				BL Black
830K 80 CRI, 3000K				GT Graphite
835K 80 CRI, 3500K				PP Pink Panache
				GH Grasshopper
				Smooth
				WHS White
				GYS Gray
				BLS Black
				COS Copper
				AMW Anti-Microbial White
				Other
				X Custom Finish

TRIM

NOC-3.5S		TRM		Lens	
Series/Category/Size/Shape	Function	Housing	Reflector Insert Color		
NOC-3.5S Noni Cylinder Family 3.5" Square	DL Downlight	TRM Trim	Texture	FRS Frosted	
	LW Lensed Wall Wash		RWH White		
		RGY Gray			
		RBL Black			
		RGT Graphite			
		RPP Pink Panache			
		RGH Grasshopper			
		Smooth			
		RWHS White			
		RGYS Gray			
		RBLS Black			
		RCOS Copper			
		RAMW Anti-Microbial White			
		Other			
		RX Custom Finish			

- Notes:
- 1 Stem length varies by canopy configuration. See Dimensions section for details
 - 2 Cable/Cord can be cut in the field to custom length
 - 3 Available only when "LW" function selected