



LWSA-4B

by CMC

Catalog ID: LWSA-4B

Cable splicing enclosure for wind turbines

- Lay-in bus bars for easy installation
- Lightweight
- Fast and easy to install - Saves Time
- Aluminum mechanical bar connector eliminates compression tools, lugs and bolt assemblies.
- Aluminum enclosure is lightweight, low maintenance and has excellent corrosion resistance.
- All-welded construction: Welds and seams are ground smooth.
- Manufactured to meet or exceed ANSI C57-12.28 for pad-mount equipment enclosure integrity.
- Removable swinging doors - Doors have stainless steel lift off hinges with stainless steel three point locking handles and recessed stainless steel penta-head bolts for security
- All mounting hardware is 18-8 stainless steel.
- Serviceable
- Customize to Meet Your Needs
- Versatile
- DLO Cable Compatible

Product Details

General

Material	Aluminum
----------	----------

Dimensions

Depth	16 in
Height	32 in
Width	32 in

Conductor Related

Conductor Range	750 Kcmil - #2 AWG
Number Of Conductors	5

Certifications and Compliance

Certification - CSA Approved	No
Certification - UL Recognized	Yes
RUS Listed Reference	No



CONNECTOR MANUFACTURING COMPANY
3501 Symmes Road
Hamilton, Ohio 45015 - 1369
513 - 860 - 4455(Press 2 for Customer Service and Sales)
To email customer Service: [jrex @cmclugs.com](mailto:jrex@cmclugs.com)

