

Adapter Panel M-2067B

Adapts M-2001 Series Digital Tapchanger Control to Replace Westinghouse SVC and SVR Controls and Beckwith Electric M-0067 Tapchanger Controls, or as a General Purpose LTC Transformer Control



- **Connects easily to the M-2001 Series Digital Tapchanger Control using four mounting screws and 24-pin connector**
- **Provides mounting adaptable to several different configurations**
- **Provides built-in CT shorting protection when the M-2001 Series Tapchanger Control is removed**



M-2067B Adapter Panel – Specification

The M-2067B is an adapter panel which, when combined with the M-2001 Series Digital Tapchanger Control, provides convenient direct replacement for Westinghouse SVC and SVR controls and Beckwith Electric M-0067 series controls. The M-2067B can also be used, with the M-2001 Series Tapchanger Control, as a general purpose LTC transformer control. The M-2067B permits changing of the M-2001 control without adapter panel removal or rewiring.

Interface

External connections are made to two terminal blocks located on the rear of the adapter panel. The second terminal block provides auxiliary functions, including self-test alarm, user-programmable alarm, manual raise/lower, operations counter and ΔVAr 2 disable.

Testing Specifications

High Voltage: All input and output terminals will withstand 1500 Vac rms to chassis or instrument ground for one minute with a leakage current not to exceed 25 mA, for all terminals to ground. Input and output circuits are electrically isolated from each other, from other circuits and from ground.

Surge Withstand Capability: All input and output circuits are protected against system transients. Units pass all requirements of ANSI/IEEE C.37.90.1-1989 defining surge withstand capability.

Radiated Electromagnetic Withstand Capability: All units are protected against electromagnetic radiated interference from portable communications transceivers.

Control Accuracy Specification: All units comply with ANSI/IEEE C57.15-1986 defining control accuracy of operation.

Environmental

Temperature Range: Functionality is maintained from -40° to $+85^{\circ}$ C.

Humidity: Functionality is maintained under 95% relative humidity (non-condensing).

Fungus Resistance: A conformal printed circuit board coating inhibits fungus growth.

Physical

Size with M-2001 Series Tapchanger Control: Overall dimensions are 16-1/2" high x 6-3/8" wide x 3-3/8" deep (41.9 cm x 16.2 cm x 8.6 cm); requires a panel cutout of 15-1/8" x 5-7/8" (38.4 cm x 14.9 cm)

Approximate Weight: 2 lbs (0.91 kg)

Approximate Shipping Weight: 5 lbs (2.27 kg)

Approximate Weight with M-2001 Series Tapchanger Control: 5 lbs, 11 oz (2.58 kg)

Approximate Shipping Weight with M-2001 Series Tapchanger Control: 10 lbs, 11 oz. (4.85 kg)

Warranty

The M-2067B Adapter Panel is covered by a five year warranty from date of shipment.

Specification subject to change without notice.

BECKWITH ELECTRIC

6190 118th Avenue North • Largo, Florida 33773-3724 U.S.A.

PHONE (727) 544-2326

beckwithelectricssupport@hubbell.com

www.beckwithelectric.com

ISO 9001:2015



A proud member of the Hubbell family.