

PDV-100 Optima Arrester (2.55 kV MCOV, 7324 Hardware)

By OHIO BRASS Catalog # 2137037324

IEEE Heavy Duty / IEC Distribution High Polymer Housed Surge Arrester



*Representative Image

Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESPTM housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

Application

Distribution

General

Bracket Type NEMA 4x5 Crossarm Bracket Cantilever Bending Strength -80 Nm

Max.

Color Gray Housing

EU RoHS Indicator Contact Manufacturer ESP™ Polymer Housing Material

Mounting Position Upright Type Distribution UPC 096359390688

Dimensions

Dimensions 9.813 in x 7.313 in x 4.875 in

5 in (127 mm)

Height 4.875 in Length 9.813 in Minimum Mounting Spacing 3 in (76.2 mm)

on Center (Sea Level) - Phase

to Ground

Minimum Mounting Spacing

on Center (Sea Level)- Phase to Phase

Stud Type 3/8-16 Weight 4.3 lb Width 7.313 in

Electrical Ratings

Creep and Leakage Distance 8.5 in (215 mm) Current - Low Current Long 250 A Duration (LCLD) Test

3 kV **Duty Cycle** Frequency Rating 48-62 Hz **MCOV** 2.55 kV Maximum .5 Microsecond 11.5 kV Discharge Volts @ Classifying

Current

Maximum Discharge Voltage • 8 kV @ 1.5 kA

7.3 kV

3.8 in

20

• 8.6 kV @ 3 kA

• 9.1 kV @ 5 kA

9.9 kV @ 10 kA

• 11.2 kV @ 20 kA

13.3 kV @ 40 kA

Maximum Switching Surge Protective Level @ 500A

Minimum Strike Pressure Relief Capability-Symmetrical rms (kA)

Time - Low Current Long

2000 µs Duration (LCLD) Test

Logistics

Pallet Quantity 192

Product Assets

Brochures - Ohio Brass Sets the Standards for Arresters (FU1587)

Catalogs - Arresters IEEE & IEC Distribution Class

(CA01065E Catalog 70)

Installation Manuals - Installation Instructions for PDV/PVR

Arresters - Chinese (17-5122C)

Installation Manuals - PDV-PVR Polymer Distribution Class

Arrester Installation Instructions (17-5122)

Installation Manuals - Installation Instructions for PDV/PVR

Arresters - French (17-5122F)

Installation Manuals - Installation Instructions for PDV/PVR

Arresters - Spanish (17-5122S)

ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc. ISO Certificates - ISO 9001:2015 - Hubbell Power Systems Inc.

Effective 2020-2023, Multi-site (English)

Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems (TD01135E)

Literature - Lightning Surge Arresters (SF01023E)

(SF14069E)
Sales Drawings - 2137037324 (Reference Only)
Video - Hubbell Power Systems Metal Oxide Varistor
(VI01022E0718)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. OB-2137037324-SPEC-EN | REV 1/2024