HUBBELL Power Systems

PDV-100 Optima Arrester (34 kV MCOV, 7214 Hardware)

By OHIO BRASS Catalog # 2137347214

IEEE Heavy Duty / IEC Distribution High Polymer Housed Surge Arrester

Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESPTM housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

Application

Distribution

General

		Time - Low Current Long	2000 Qs
Bracket Type	None	Duration (LCLD) Test	
Cantilever Bending Strength -	80 Nm		
Max.		Certifications And Compliance	
Catalog Number	2137347214		
Color	Gray Housing	Industry Standard(s)	IEEE/IEC
EU RoHS Indicator	Contact Manufacturer		
Material	ESP™ Polymer Housing	Logistics	
Mounting Position	Upright	Pallet Quantity	56
Туре	Distribution		
UPC	096359415107	Product Assets	
Dimensions		Catalogs - Arresters IEEE & IEC Distribution Class	
		ISO Certificates - ISO 14001:201	15 - Hubbell Power Systems Inc.
Height	17.2 in	Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems	
Stud Type	3/8-16		
		Literature - Hubbell Arrester and Wildlife Guard Solution Kits	
Electrical Ratings		Specifications - Specification for IEEE Heavy Duty Class	
Creep and Leakage Distance	56.2 in (1427 mm)	Distribution Arresters	
		Specifications - 2137347214	

Video - Hubbell Power Systems Metal Oxide Varistor





*Representative Image

250 A

42 kV

34 kV

142 kV

137.7 kV

2000 00

20

48-62 Hz

• 102.7 kV @ 1.5 kA

• 110 kV @ 3 kA

• 116.5 kV @ 5 kA

• 127 kV @ 10 kA

144.3 kV @ 20 kA
170.1 kV @ 40 kA

Current - Low Current Long

Maximum .5 Microsecond

Discharge Volts @ Classifying

Maximum Discharge Voltage

Maximum Switching Surge

Protective Level @ 500A

Pressure Relief Capability-

Time Low Current Long

Symmetrical rms (kA)

Duration (LCLD) Test

Frequency Rating

Duty Cycle

MCOV

Current

©2025 Hubbell Incorporated. All rights reserved OB-2137347214-SPEC-EN | REV 3/2025