## HUBBELL **Power Systems**

# PVR Optima (10.2 kV MCOV, 7202 Hardware)

By OHIO BRASS Catalog # 2216107202

IEEE Riser Pole Class Polymer Housed Surge Arrester

### Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESP<sup>TM</sup> housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- · Arresters assembled in Aiken, South Carolina
- 100% routine tested

### Application

Distribution

#### General

Bracket Type	None	Symmetrical rms (kA) Time - Low Current Long	2000 Qs
Cantilever Bending Strength - Max.	135 Nm	Duration (LCLD) Test	2000 43
Catalog Number	2216107202	Certifications And Compliance	
Color	Gray Housing	-	
EU RoHS Indicator	Contact Manufacturer	Industry Standard(s)	IEEE
Material Mounting Position	ESP™ Polymer Housing Upright	Logistics	
Туре	Distribution	Pallet Quantity	192
UPC	096359417958		
Dimensions		Product Assets	
Dimensions		Catalogs - Arresters IEEE & II	FC Distribution Cl
Height	9.4 in	ISO Certificates - ISO 14001:2015 - Hubbell Po	
Stud Type	3/8-16	Literature - Hubbell Arrester and Wildlife Guar Literature - Application Guide: Metal-oxide Su	
Electrical Ratings		use on AC systems	
Creep and Leakage Distance	26 in (660 mm)	Specifications - 2216107202	
		Video - Hubbell Power Systems Metal Oxide V	



Current - Low Current Long Duration (LCLD) Test	250 A			
Duty Cycle	12 kV			
Frequency Rating	48-62 Hz			
MCOV	10.2 kV			
Maximum .5 Microsecond	36.2 kV			
Discharge Volts @ Classifying				
Current				
Maximum Discharge Voltage	• 27.8 kV @ 1.5 kA			
	• 29 kV @ 3 kA			
	• 30.2 kV @ 5 kA			
	• 32.5 kV @ 10 kA			
	• 35.9 kV @ 20 kA			
	• 41.6 kV @ 40 kA			
Maximum Switching Surge	23.9 kV			
Protective Level @ 500A				
Minimum Strike	6.1 in			
Pressure Relief Capability-	20			
Symmetrical rms (kA)				
Time - Low Current Long	2000 Qs			
Duration (LCLD) Test				
Certifications And Compliance				

Class ower Systems Inc. ard Solution Kits urge Arresters for Varistor

