HUBBELL Power Systems

PVR Optima (10.2 kV MCOV, 7514 Hardware)

By OHIO BRASS Catalog # 2216107514

IEEE Riser Pole Class Polymer Housed Surge Arrester



*Representative Image

250 A

36.2 kV

Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESPTM housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- · Arresters assembled in Aiken, South Carolina
- 100% routine tested

Application

Distribution

General

Bracket Type None
Cantilever Bending Strength - 135 Nm

Мах.

Catalog Number 2216107514
Color Gray Housing

Material ESP™ Polymer Housing

Mounting Position Upright
Type Distribution
UPC 096359671732

Dimensions

Height 9.4 in Stud Type 3/8-16

Electrical Ratings

Creep and Leakage Distance 26 in (660 mm)

Current - Low Current Long

Duration (LCLD) Test

Duty Cycle 12 kV
Frequency Rating 48-62 Hz
MCOV 10.2 kV

Maximum .5 Microsecond
Discharge Volts @ Classifying

Current

Maximum Discharge Voltage • 27.8 kV @ 1.5 kA

29 kV @ 3 kA30.2 kV @ 5 kA

• 32.5 kV @ 10 kA

35.9 kV @ 20 kA41.6 kV @ 40 kA

Maximum Switching Surge 23.9 kV

Protective Level @ 500A

Minimum Strike 6.1 in
Pressure Relief Capability
Symmetrical rms (kA)

Time - Low Current Long 2000 Qs

Duration (LCLD) Test

Certifications And Compliance

Industry Standard(s) IEEE

Logistics

Pallet Quantity 192

Product Assets

Catalogs - Arresters IEEE & IEC Distribution Class

ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc. Literature - Hubbell Arrester and Wildlife Guard Solution Kits Literature - Application Guide: Metal-oxide Surge Arresters for

use on AC systems

Specifications - 2216107514

Video - Hubbell Power Systems Metal Oxide Varistor

