

# PVR Optima (10.2 kV MCOV, 7533 Hardware)

By OHIO BRASS Catalog # 2216107533

IEEE Riser Pole Class Polymer Housed Surge Arrester



- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESP<sup>TM</sup> housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

# Application

Distribution

### General

| Bracket Type                  | Transformer Bracket  |
|-------------------------------|----------------------|
| Cantilever Bending Strength - | 135 Nm               |
| Max.                          |                      |
| Color                         | Gray Housing         |
| EU RoHS Indicator             | Contact Manufacturer |
| Material                      | ESP™ Polymer Housing |
| Mounting Position             | Upright              |
| Туре                          | Distribution         |
| UPC                           | 096359418016         |
| Dimensione                    |                      |
| Dimensions                    |                      |
| Height                        | 9.4 in               |
| Stud Type                     | 3/8-16               |



# **Electrical Ratings**

| Creep and Leakage Distance   | 15.4 in (391 mm)   |
|--|--------------------|
| Current - Low Current Long   | 250 A              |
| Duration (LCLD) Test   |                    |
| Duty Cycle   | 12 kV              |
| Frequency Rating   | 48-62 Hz           |
| MCOV   | 10.2 kV            |
| Maximum .5 Microsecond<br>Discharge Volts @ Classifying<br>Current | 36.2 kV            |
| Maximum Discharge Voltage  | • 27.8 kV @ 1.5 kA |
|  | • 29 kV @ 3 kA     |
|  | • 30.2 kV @ 5 kA   |
|  | • 32.5 kV @ 10 kA  |
|  |                    |

35.9 kV @ 20 kA
41.6 kV @ 40 kA

Maximum Switching Surge<br/>Protective Level @ 500A23.9 kVMinimum Strike6.1 inPressure Relief Capability-<br/>Symmetrical rms (kA)20Time - Low Current Long<br/>Duration (LCLD) Test2000 µs

# Logistics

Pallet Quantity

### Product Assets

Brochures - Ohio Brass Sets the Standards for Arresters (EU1587) Catalogs - Arresters IEEE & IEC Distribution Class (CA01065E\_Catalog 70) Installation Manuals - PDV-PVR Polymer Distribution Class Arrester Installation Instructions (17-5122) Installation Manuals - Installation Instructions for PDV/PVR Arresters - Chinese (17-5122C) Installation Manuals - Installation Instructions for PDV/PVR Arresters - French (17-5122F) Installation Manuals - Installation Instructions for PDV/PVR Arresters - Spanish (17-5122S) ISO Certificates - ISO 9001:2015 - Hubbell Power Systems Inc. Effective 2020-2023, Multi-site (English) ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc. Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems (TD01135E) Literature - Lightning Surge Arresters (SF01023E) Literature - Hubbell Arrester and Wildlife Guard Solution Kits

192

HUBBELL

A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. OB-2216107533-SPEC-EN | REV 1/2024