HUBBELL Power Systems

PVR Optima (29 kV MCOV, 7224 Hardware)

By OHIO BRASS Catalog # 2216297224

IEEE Riser Pole Class Polymer Housed Surge Arrester

Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESPTM housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

Application

Distribution

General

NEMA 4x5 Crossarm Bracket 135 Nm
2216297224
Gray Housing
Contact Manufacturer
ESP™ Polymer Housing
Upright
Distribution
096359418870

Dimensions

Height	15.3 in
Stud Type	3/8-16

Electrical Ratings

Creep and Leakage Distance

49 in (1245 mm)



*Representative Image

Current - Low Current Long	250 A	
Duration (LCLD) Test Duty Cycle	36 kV	
Frequency Rating	48-62 Hz	
MCOV	29 kV	
Maximum .5 Microsecond	107.2 kV	
Discharge Volts @ Classifying		
Current		
Maximum Discharge Voltage	• 82.2 kV @ 1.5 kA	
	 85.6 kV @ 3 kA 89.2 kV @ 5 kA 	
	 89.2 kV @ 5 kA 96.1 kV @ 10 kA 	
	 106.2 kV @ 20 kA 	
	• 123 kV @ 40 kA	
Maximum Switching Surge	70.7 kV	
Protective Level @ 500A		
Minimum Strike	18 in	
Pressure Relief Capability-	20	
Symmetrical rms (kA) Time - Low Current Long	2000 Qs	
Duration (LCLD) Test	2000 Q3	
Certifications And Compliance		
Industry Standard(s)	IEEE	
Logistics		
-		
Pallet Quantity	35	
Product Assets		
Catalogs - Arresters IEEE & IEC Distribution Class		
ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc.		
Literature - Application Guide: Metal-oxide Surge Arresters for		
use on AC systems		

Literature - Hubbell Arrester and Wildlife Guard Solution Kits Specifications - 2216297224

Video - Hubbell Power Systems Metal Oxide Varistor

