HUBBELL Power Systems

PDV-65 Optima Arrester (2.55 kV MCOV, C4CC Hardware)

By OHIO BRASS Catalog # 294003C4CC

IEEE Normal Duty Class / IEC Distribution Medium Polymer Housed Surge Arrester



*Representative Image

75 A

Features

- Over 35 years of excellent field performance with over 40 million distribution arresters installed
- Long lasting ESPTM housing material with superior mechanical strength and electrical characteristics
- Reliable capacitive disconnector operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- · Arresters assembled in Aiken. South Carolina
- 100% routine tested

Application

Distribution

General

Bracket Type None
Cantilever Bending Strength - 33.192 lb.

Max.

Catalog Number 294003C4CC Color Gray Housing

EU RoHS Indicator Contact Manufacturer

Material ESP™ Polymer Housing

Mounting Hardware Insulating Bracket with

Disconnector

Mounting Position Upright
Type Distribution

Dimensions

Height 4.9 in Maximum Operating Altitude 12000 ft

Electrical Ratings

Creep and Leakage Distance 13.3 in (338 mm)

Current - Low Current Long

Duration (LCLD) Test

Duty Cycle 3 kV
Frequency Rating 48-62 Hz
MCOV 2.55 kV
Maximum .5 Microsecond 10.5 kV

Discharge Volts @ Classifying

Current

Maximum Discharge Voltage

8.1 kV @ 1.5 kA

• 8.7 kV @ 3 kA

9.2 kV @ 5 kA10.4 kV @ 10 kA

• 12 kV @ 20 kA

• 15 kV @ 40 kA

6.1 in

2000 Qs

Maximum Switching Surge 7.3 kV

Protective Level @ 500A

Minimum Strike

Pressure Relief Capability-

Symmetrical rms (kA)

Time - Low Current Long

Duration (LCLD) Test

Certifications And Compliance

Industry Standard(s) IEEE/IEC

Logistics

Pallet Quantity 224

Product Assets

Brochures - Ohio Brass Sets the Standards for Arresters

Catalogs - Arresters IEEE & IEC Distribution Class

Installation Manuals - PDV-PVR Polymer Distribution Class

Arrester Installation Instructions

Specifications - Specification for IEEE Normal Duty Class

Distribution Arresters

Specifications - 294003C4CC

