

Protecta*Lite Arrester (8.4 kV MCOV)

By OHIO BRASS Catalog # 602009B0X1003

This web listing represents a sampling of typical configurations. Protecta*Lite Arrester assemblies can be customized for all distribution and transmission lines.

Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltage

Example: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage.

For more information about arrester selection, please contact your Hubbell Power Systems representative.



*Representative Image

Features

- Eliminate lightning interruptions with Protecta*Lite Arresters
- Custom designs available up to 765 kV
- Protecta*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta*Lite improves line performance, click here to visit our blog.

Application

35 kV and Below

General

Type	Line Arresters
UPC.	096359627425

Dimensions

Dimensions	10.313 in x 10.313 in x 13.750 in
Height	13.750 in
Length	10.313 in
Weight	2.2 lb
Width	10.313 in

Electrical Ratings

Creep and Leakage Distance	14.4 in (365.8 mm)
Duty Cycle	10 kV
Frequency Rating	48-62 Hz
MCOV	8.4 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	34.0 kV
Maximum Discharge Voltage	• 25.4 kV @ 1.5 kA
	• 27.1 kV @ 3 kA

28.8 kV @ 5 kA31.6 kV @ 10 kA

35.6 kV @ 20 kA42.3 kV @ 40 kA

Maximum Switching Surge 24.4 kV
Protective Level @ 500A
Pressure Relief CapabilitySymmetrical rms (kA)

Voltage - Line 13.8 kV

Certifications and Compliance

Industry Standard(s) IEEE/IEC

Product Assets

Case Studies - Performance & Revenue Enhancements
Utilizing Line Surge Arresters - White Paper (CH01070E)
Catalogs - Protecta*Lite Line Surge Arresters (35) (CA01130E)
ISO Certificates - ISO 9001:2015 - Hubbell Power Systems Inc.
Effective 2020-2023, Multi-site (English)
ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc.
Literature - Protecta*Lite (SF08019E)
Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems (TD01135E)

use on AC systems (TD01135E)
Literature - Protecta*Lite Line Arrester Performance Study

(SF01064E)
Sales Drawings - 602009B0X1003 (Reference Only)
Video - Hubbell Power Systems Metal Oxide Varistor

Video - Ohio Brass Protecta*Lite® Systems Surge Arresters (VI01020E0118)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. OB-602009B0X1003-SPEC-EN | REV 1/2024