## HUBBELL **Power Systems**

# Protecta\*Lite Arrester (8.4 kV MCOV)

By OHIO BRASS Catalog # 602009B0X4001

This web listing represents a sampling of typical configurations. Protecta\*Lite Arrester assemblies can be customized for all distribution and transmission lines.

Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltage

Example: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage.

For more information about arrester selection, please contact your Hubbell Power Systems representative.

#### Features

- Eliminate lightning interruptions with Protecta\*Lite Arresters
- Custom designs available up to 765 kV
- Protecta\*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta\*Lite improves line performance, click here to visit our blog.

#### Application

Above 35 kV

#### General

		Pallet Quantity 112
Catalog Number	602009B0X4001	
Installation Type	Suspension	Product Assets
Insulator Type	None	
Туре	Line Arresters	Case Studies - Performance & Revenue Enhancements Utiliz
UPC	096359605713	Line Surge Arresters - White Paper
		Catalogs - Protecta*Lite Line Surge Arresters
Electrical Ratings		Installation Manuals - Installation Instructions Protecta*Lite
-		Arresters - English
Creep and Leakage Distance	14.4 in (365.8 mm)	Installation Manuals - Installation Instructions Protecta*Lite
Duty Cycle	10 kV	Arresters - Spanish
Frequency Rating	48-62 Hz	ISO Certificates - ISO 14001:2015 - Hubbell Power Systems II
MCOV	8.4 kV	Literature - Protecta*Lite
Maximum .5 Microsecond	34 kV	Literature - Protecta*Lite Line Arrester Performance Study
Discharge Volts @ Classifying		Literature - Application Guide: Metal-oxide Surge Arresters
Current		use on AC systems
Maximum Discharge Voltage	• 25.4 kV @ 1.5 kA	Specifications - 602009B0X4001
	• 27.1 kV @ 3 kA	
	• 28.8 kV @ 5 kA	Technical Publications - The Evolution of Line Surge Arreste
	<ul> <li>31.6 kV @ 10 kA</li> </ul>	Technology
	· JIOKV @ IOKA	



	• 35.6 kV @ 20 kA
	• 42.3 kV @ 40 kA
Maximum Switching Surge	24.4 kV
Protective Level @ 500A	
Pressure Relief Capability-	20
Symmetrical rms (kA)	
Voltage - Line	13.8 kV

### **Certifications And Compliance**

Industry Standard(s)	IEEE/IEC

#### Logistics

Pallet Quantity 110

zing Inc. for er



©2024 Hubbell Incorporated. All rights reserved OB-602009B0X4001-SPEC-EN | REV 10/2024