

Protecta*Lite Arrester (15.3 kV MCOV)

By OHIO BRASS Catalog # 602015B0X1002

This web listing represents a sampling of typical configurations. Protecta*Lite Arrester assemblies can be customized for all distribution and transmission lines.

Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltage

Example: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage.

For more information about arrester selection, please contact your Hubbell Power Systems representative.

Features

- Eliminate lightning interruptions with Protecta*Lite

 Arrestors
- Custom designs available up to 765 kV
- Protecta*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta*Lite improves line performance, click here to visit our blog.

Application

35 kV and Below

General

Type Line Arresters

Electrical Ratings

Creep and Leakage Distance 25.2 in (640.1 mm)

Duty Cycle 18 kV

Frequency Rating 48-62 Hz
MCOV 15.3 kV
Maximum .5 Microsecond 60.6 kV

Discharge Volts @ Classifying

Maximum Discharge Voltage

• 45.4 kV @ 1.5 kA

48.4 kV @ 3 kA

• 51.3 kV @ 5 kA

• 56.4 kV @ 10 kA

• 63.5 kV @ 20 kA

• 75.5 kV @ 40 kA

Maximum Switching Surge Protective Level @ 500A

Pressure Relief Capability-Symmetrical rms (kA)

Voltage - Line 23 kV

43.5 kV

20



*Representative Image

Certifications and Compliance

Industry Standard(s) IEEE/IEC

Logistics

Pallet Quantity 112

Product Assets

Case Studies - Performance & Revenue Enhancements Utilizing Line Surge Arresters - White Paper (CH01070E) Catalogs - Protecta*Lite Line Surge Arresters (35) (CA01130E) ISO Certificates - ISO 9001:2015 - Hubbell Power Systems Inc. Effective 2020-2023, Multi-site (English)

ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc.

Literature - Protecta*Lite (SF08019E)

Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems (TD01135E)

Literature - Protecta*Lite Line Arrester Performance Study (SF01064E)

Video - Hubbell Power Systems Metal Oxide Varistor (VIO1022E0718)

Video - Ohio Brass Protecta*Lite® Systems Surge Arresters (VI01020E0118)

