HUBBELL **Power Systems**

Protecta*Lite Arrester (15.3 kV MCOV)

By OHIO BRASS Catalog # 602015B0X4005

This web listing represents a sampling of typical configurations. Protecta*Lite Arrester assemblies can be customized for all distribution and transmission lines.

Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltage

Example: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage.

For more information about arrester selection, please contact your Hubbell Power Systems representative.

Features

- Eliminate lightning interruptions with Protecta*Lite Arresters
- Custom designs available up to 765 kV
- Protecta*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta*Lite improves line performance, click here to visit our blog.

Application

35 kV and Below

General

Catalog Number Installation Type	602015B0X4005 Suspension	Product Assets
Type UPC	Line Arresters 096359527015	Case Studies - Performance & Revenue Enhancements Utilizing Line Surge Arresters - White Paper
Electrical Ratings		Catalogs - Protecta*Lite Line Surge Arresters ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc.
Creep and Leakage Distance Duty Cycle Frequency Rating MCOV Maximum .5 Microsecond Discharge Volts @ Classifying Current	25.2 in (640.1 mm) 18 kV 48-62 Hz 15.3 kV 60.6 kV	Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems Literature - Protecta*Lite Literature - Protecta*Lite Line Arrester Performance Study Specifications - 602015B0X4005 Technical Publications - The Evolution of Line Surge Arrester Technology
Maximum Discharge Voltage	• 45.4 kV @ 1.5 kA	Video - Hubbell Power Systems Metal Oxide Varistor Video - Ohio Brass Protecta*Lite® Systems Surge Arresters



	• 48.4 kV @ 3 kA
	• 51.3 kV @ 5 kA
	• 56.4 kV @ 10 kA
	• 63.5 kV @ 20 kA
	• 75.5 kV @ 40 kA
Maximum Switching Surge	43.5 kV
Protective Level @ 500A	
Pressure Relief Capability-	20
Symmetrical rms (kA)	
Voltage - Line	23 kV

Certifications And Compliance

Industry Standard(s) IEEE/IEC



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved OB-602015B0X4005-SPEC-EN | REV 10/2024