HUBBELL **Power Systems**

Protecta*Lite Arrester (84 kV MCOV)

BV OHIO BRASS Catalog # 642084G1G2004

This web listing represents a sampling of typical configurations. Protecta*Lite Arrester assemblies can be customized for all distribution and transmission lines.

Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltage

Example: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage.

For more information about arrester selection, please contact your Hubbell Power Systems representative.

Features

- Eliminate lightning interruptions with Protecta*Lite Arresters
- Custom designs available up to 765 kV
- Protecta*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta*Lite improves line performance, click here to visit our blog.

Application

Above 35 kV

General

Catalog Number Installation Type	642084G1G2004 Deadend	Product Assets
Type UPC	Line Arresters 096359507130	Case Studies - Performance & Revenue Enhancements Utilizing Line Surge Arresters - White Paper
Electrical Ratings		Catalogs - Protecta*Lite Line Surge Arresters ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc.
Creep and Leakage Distance	140.6 in (3571.2 mm)	Literature - Protecta*Lite
Duty Cycle	108 kV	Literature - Protecta*Lite Line Arrester Performance Study
Frequency Rating	48-62 Hz	Literature - Application Guide: Metal-oxide Surge Arresters for
MCOV	84 kV	use on AC systems
Maximum .5 Microsecond	341.5 kV	Specifications - 642084G1G2004
Discharge Volts @ Classifying		Technical Publications - The Evolution of Line Surge Arrester
Current		Technology
Maximum Discharge Voltage	• 255.5 kV @ 1.5 kA	Video - Hubbell Power Systems Metal Oxide Varistor
	\sim	Video - Ohio Brass Protecta*Lite® Systems Surge Arresters



	• 272.5 kV @ 3 kA
	• 289 kV @ 5 kA
	• 317.5 kV @ 10 kA
	• 357 kV @ 20 kA
	• 425 kV @ 40 kA
Maximum Switching Surge	245 kV
Protective Level @ 500A	
Pressure Relief Capability-	20
Symmetrical rms (kA)	
Voltage - Line	138 kV

Certifications And Compliance

Industry Standard(s) IEEE/IEC



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved OB-642084G1G2004-SPEC-EN | REV 3/2025