HUBBELL **Power Systems**

Protecta*Lite Arrester (42 kV MCOV)

BV OHIO BRASS Catalog # 682042H1G2002

This web listing represents a sampling of typical configurations. ProtectaLite Arrester assemblies can be customized for all distribution and transmission lines. Selection of arrester MCOV size is based upon the maximum continuous voltage that is applied across the arrester in service (line-to-ground). For arresters on effectively grounded neutral systems, this is normally the maximum line-to-ground voltageExample: 84 kV on a 138 kV system. For ungrounded or impedance-grounded systems, the MCOV should be at least 90 percent of maximum phase-to-phase voltage. For more information about arrester selection, please contact your Hubbell Power Systems representative.

Features

- Eliminate lightning interruptions with Protecta*Lite Arresters
- Custom designs available up to 765 kV
- Protecta*Lite Arresters offer protection on both shielded and unshielded lines
- To learn more about how Protecta*Lite improves line performance, click here to visit our blog.

Application

Above 35 kV

General

| Catalog Number EU RoHS Indicator | 682042H1G2002 Contact Manufacturer | Product Assets |
|--|---|---|
| Installation Type Type UPC | Horizontal Post Assembly Line Arresters 096359501992 | Case Studies - Performance & Revenue Enhancements Utilizing Line Surge Arresters - White Paper Catalogs - Protecta*Lite Line Surge Arresters |
| Electrical Ratings | | ISO Certificates - ISO 14001:2015 - Hubbell Power Systems Inc. Literature - Protecta*Lite |
| Creep and Leakage Distance Duty Cycle Frequency Rating MCOV Maximum .5 Microsecond Discharge Volts @ Classifying Current | 70.7 in (1795.8 mm) 54 kV 48-62 Hz 42 kV 170.6 kV | Literature - Protecta*Lite Line Arrester Performance Study Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems Specifications - 682042H1G2002 Technical Publications - The Evolution of Line Surge Arrester Technology Video - Hubbell Power Systems Metal Oxide Varistor |
| Maximum Discharge Voltage | • 127.6 kV @ 1.5 kA | Video - Ohio Brass Protecta*Lite® Systems Surge Arresters |



| Maximum Switching Surge Protective Level @ 500A Pressure Relief Capability- | 178.4 kV @ 20 kA 212.3 kV @ 40 kA 122.4 kV | | |
|---|--|--|--|
| Symmetrical rms (kA) Voltage - Line | 69 kV | | |
| Certifications And Compliance | | | |
| Industry Standard(s) | IEEE/IEC | | |

©2025 Hubbell Incorporated. All rights reserved

• 136.1 kV @ 3 kA

• 144.4 kV @ 5 kA

• 158.6 kV @ 10 kA

