## HUBBELL **Power Systems**

# EVP Arrester (88 kV MCOV / Uc)

By OHIO BRASS Catalog # EVP0088003002

IEEE Station Class / IEC Station Medium Polymer Housed Surge Arrester

### Features

- EVP solid core station arresters comply with the latest revision of IEEE C62.11 and IEC 60099-4
- Long lasting ESP<sup>TM</sup> housing material with superior mechanical strength and electrical characteristics
- Robust sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Assembled in Aiken, South Carolina
- 100% routine tested

### General

Cantilever Bending Strength -	20,000 lb.
Max.	
Catalog Number	EVP0088003002
Color	Gray Housing
Material	ESP™ Polymer Housing
Mounting Hardware	Single Eyebolt Terminals
Mounting Position	Upright
Туре	Station
UPC	096359676447

### Dimensions

Diameter - Bolt Circle Variable	8.75 to 10 in	Industry Standard(s)	IEEE/IEC
Diameter - Lug Hole Diameter - Single Bolt Hole(s)	.56 in (14.224 mm) 0.5 in	Product Assets	
Height Maximum Operating Altitude Minimum Mounting Spacing on Center (Sea Level) - Phase to	46.3 in 12000 ft 28.2 in (716 mm)	Catalogs - Station Class Surge Arresters IEEE and IEC Installation Manuals - EVP Polymer Station Class Arrest Installation Instructions ISO Certificates - ISO 14001:2015 - Hubbell Power Syste	
Minimum Mounting Spacing on Center (Sea Level)- Phase to Phase	35.6 in (904 mm)	Literature - Polymer Station	
Thickness - Lug Weight	1.25 in (31.75 mm) 59 lb	Sales Drawings - EVP0088 Specifications - Specification	003002 (for reference only) on for Solid Core IEC Station
Electrical Ratings		Arresters Specifications - EVP00880	03002





123 in (3124 mm)

Duty Cycle	108 kV
Frequency Rating	48-62 Hz
MCOV	88 kV
Maximum .5 Microsecond	289 kV
Discharge Volts @ Classifying	
Current	
Maximum Discharge Voltage	• 221.2 kV @ 1.5 kA
	• 232.5 kV @ 3 kA
	• 243.7 kV @ 5 kA
	• 261.5 kV @ 10 kA
	• 282.7 kV @ 20 kA
	• 322.4 kV @ 40 kA
Maximum Switching Surge	207.4 kV
Protective Level @ 500A	
Pressure Relief Capability-	63
Symmetrical rms (kA)	
Withstand Voltage - 60 Hz Wet	275 kV
Withstand Voltage - Lightning	631 kV
Impulse	

Withstand Voltage - Switching 529 kV Impulse

#### **Certifications And Compliance**

Creep and Leakage Distance

Impulse

ation Class Arrester bbell Power Systems Inc. oxide Surge Arresters for or reference only) d Core IEC Station Class Specifications - EVP0088003002 Video - Hubbell Power Systems Metal Oxide Varistor