HUBBELL
Power Systems

Quadri*Sil Horizontal Line Post Insulator

By OHIO BRASS
Catalog # P250036S9030

2.5″ Line Post, Standard Leak, Long Two Hole Blade, Aluminum Flat Base with 12″ CL, 8″x10″, and 8″x13″ holes for 7/8″ bolts

*Representative Image

Features

Made from hydrophobic silicone polymer

General

Cantilever Bending Strength - Max.	3830 LB
Cantilever Bending Strength - Routine	1915 LB
Catalog Number	P250036S9030
Fitting - Ground End	Aluminum Flat
Fitting - Live Line End	Long Tear Drop Blade
Number of Sheds	30
Shed Style	Uniform

Dimensions

Diameter - Shed(s)	5.06
Length	12 in
Length - Effective	55.9 in
Rod Diameter	2.5 in
Thickness - Housing	> 3MM

Electrical Ratings

Arc Distance - Dry	37.1 IN (942 MM)
Creep and Leakage Distance	95 IN (2413 MM)
Critical Impulse Flashover (CIFO) - Negative	690
Critical Impulse Flashover (CIFO) - Positive	580
Flashover Voltage - 60 Hz Dry	380
Flashover Voltage - 60 Hz Wet	345
kV Class	138 kV

Product Assets

Catalogs - Quadri*Sil Suspension & Line Post Insulators Catalog
Specifications - P250036S9030
Test Documents - ANSI C29.17 Prototype Test Report; Quadri*Sil Line Post Insulators – 2.5” Rod

©2024 Hubbell Incorporated. All rights reserved