

HUBBELL

Power Systems

Quadri*Sil Vertical Line Post Insulator

By OHIO BRASS
Catalog # [P250038S2050](#)

2.5" Line Post, Standard Leak, Vertical Clamptop, 5" Bolt Circle with 5/8" Thru Holes



Features

Made from hydrophobic silicone polymer

General

| | |
|---------------------------------------|----------------------------------|
| Cantilever Bending Strength - Max. | 3520 LB |
| Cantilever Bending Strength - Routine | 1760 LB |
| EU RoHS Indicator | Contact Manufacturer |
| Fitting - Ground End | 5" Bolt Circle, 5/8" tapped hole |
| Fitting - Live Line End | Vertical Clamptop |
| Number of Sheds | 32 |
| Shed Style | Uniform |
| UPC | 096359442097 |

Dimensions

| | |
|---------------------|---------|
| Diameter - Shed(s) | 5.06 |
| Length - Effective | 49.5 in |
| Rod Diameter | 2.5 in |
| Thickness - Housing | > 3MM |

Electrical Ratings

| | |
|--|-------------------|
| Arc Distance - Dry | 39.5 IN (1003 MM) |
| Creep and Leakage Distance | 101 IN (2565 MM) |
| Critical Impulse Flashover (CIFO) - Negative | 730 |
| Critical Impulse Flashover (CIFO) - Positive | 615 |
| Flashover Voltage - 60 Hz Dry | 410 |
| Flashover Voltage - 60 Hz Wet | 370 |
| kV Class | 138 kV |

Product Assets

[Catalogs - Quadri*Sil Suspension & Line Post Insulators Catalog](#)
[Test Documents - ANSI C29.17 Prototype Test Report; Quadri*Sil Line Post Insulators - 2.5" Rod](#)



A Hubbell brand