HUBBELL **Power Systems**

POC 88 Series Bushing - 69kV

By PCORE Electric Catalog # B-88013-70

POC® 69kV-400A/1200A Transformer-Circuit Breaker Bushing, Paper-Oil-Capacitor Type, Rated per IEEE C57.19.01, Draw-lead Connected/Bottom Connected for Air-to-Oil Applications, 21.00" Min. Oil Immersion Level



*Representative Image

Features

- Paper oil capacitor wound core with external porcelain insulator
- High seismic

General

Application Bottom Terminal Type Color	Transformer-Oil Circuit Breaker Threaded w/ Hole Gray
Immersion Type - Above	Air
Flange	
Immersion Type - Below Flange	Oil
Material - Flange	Aluminum
Material - Insulation	Porcelain
Mounting Position	Vertical
Number of Flange Mounting	6
Holes	
Test Tap	Yes
Top Terminal Plating	Silver Plated
Top Terminal Type	Threaded
Type	Condenser Bushings

Dimensions

Above Flange Length	35.06 in
Below Flange Length	37.5 in
Diameter - Below Flange	5.25 in
Maximum D <gt></gt> 1"	
Diameter - Below Flange	6.00 in
Maximum P	
Diameter - Bottom Terminal	1 1/2-12
Outside	
Diameter - Live Part Top	7.25 in
Diameter - Top Terminal	1 1/2-12
Outside	
Dimensions	72.56 in x 11.00 in x 72.56 in
Effective Length - Bottom	2.12 in
Terminal	
Effective Length - Top Terminal	2.50 in
Flange Mounting Hole Bolt	9.25 in
Circle	
Flange Mounting Hole Diameter	0.88 in
Flange Outside Diameter	11 in
Height	72.56 in
Length	72.56 in
Length - Drawlead Above	31.12 in
Flange	
Length - Ground Shield	21.00 in
Length - Live Part Top	7.25 in
Length - Minimum Oil	21.00 in
Immersion Level	
Sealing Surface Outside	8.25 in
Diameter	
Stud Inside Diameter	0.88 in
Weight	155 lb
Width	11 in
Electrical Ratings	

BIL Current Rating	350 kV 400 A
	1200 A
Minimum Creepage	54 in
Minimum Strike	24 in
kV Class	69 kV

Certifications And Compliance

Industry Standard(s)

IFFF

Product Assets

Catalogs - PCORE® Capacitance-Graded Bushings, Test Terminals and Services Installation Manuals - Instruction Manual for POC® Bushings Sales Drawings - POC Bushing

