

FSP Adapter Panel, Blank

By Hubbell Premise Wiring
Catalog # [FSPNB](#)



Features

-
-
-

Application

Interconnect

Performance

- Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical)
- Environmental - Operating temperature - 0 °C to +75 °C

General

Adapter Type	Blank
Catalog Number	FSPNB
Color	Black
Environmental Conditions	Indoor
Item Type	Blank
Material - Mounting Hardware	Snap-In

Service Life	500 matings
Sub Brand	OptiChannel
Temperature Rating	-40C to +85C
UPC	662620671659

Certifications And Compliance

Industry Standard(s)	- TIA-568-C.3 - TIA-604-FOCIS
----------------------	---

Logistics

Carton Quantity	4
Pallet Quantity	1800

Product Assets

[Catalog Page - PREM G11 Catalog Page](#)
[Catalog Page - PREM G9 CatalogPage](#)
[Catalogs - Premise Wiring Catalog](#)
[Engineering Drawing - PREMISE_HWS14976C_ACAD](#)
[Literature - FIBERHUBB N-Series Fiber Panels](#)
[Sales Drawings - PREMISE_HWS14976C_SALESDRAWING](#)
[Specifications - FSPNB](#)